

### **INSTRUMENT PROCESSING SHEET**

□H/D □CMI □EE	
Performed By	
mm	
3mm	
03mm	
Verification (L/s)	
32 mm (.13916 36 mm (.15619	
(.156190)	
(.228278)	
(.447547)	
Performed By	
ment	
or Replacement	
lacement	
les Dantes de S.C. 1	
ks Performed By MH	
22.69 rm. ID#: 300918	
MD/062	
erial #: MP4863	
erial #: MP4864	
erial #: MP4864 erial #: MP5097	
erial #: MP4864 erial #: MP5097  Performed By MH	
erial #: MP4864 erial #: MP5097	
erial #: MP4864 erial #: MP5097  Performed By MH	
erial #: MP4864 erial #: MP5097  Performed By MH	
erial #: MP4864 erial #: MP5097  Performed By MH	
erial #: MP4864 erial #: MP5097  Performed By MH  1017	
erial #: MP4864 erial #: MP5097  Performed By MH  1017	
Performed By MH  1017    umber SD1014	
Performed By MH  1017    SD1014   SD1015	
Performed By MH  1017  SD1014 SD1015 MP4863	
Performed By MH  1017    SD1014   SD1015   MP4863   MP4864   MP4864   MP4864	
Perial #: MP4864 erial #: MP5097  Performed By MH  1017  Jumber SD1014 SD1015 MP4863 MP4864 MP5097	
Perial #: MP4864 erial #: MP5097  Performed By MH  1017  lumber SD1014 SD1015 MP4863 MP4864 MP5097 Stability Checks	
Performed By MH  1017  SD1014 SD1015 MP4863 MP4864 MP5097  S-Stability Checks (Calibration	
Performed By MH  1017  SD1014 SD1015 MP4863 MP4864 MP5097  Stability Checks (Calibration n 40	
Performed By MH  1017  SD1014 SD1015 MP4863 MP4864 MP5097  S-Stability Checks (Calibration	
Perial #: MP4864 Perial #: MP5097  Performed By MH  1017  Iumber SD1014 SD1015 MP4863 MP4864 MP5097  E-Stability Checks Calibration 140 Per	
Perial #: MP4864 Perial #: MP5097  Performed By MH  1017  Dumber SD1014 SD1015 MP4863 MP4864 MP5097  Personal Processor Calibration In 40 Personal Processor Ca	
Perial #: MP4864 Perial #: MP5097  Performed By MH  1017  Iumber SD1014 SD1015 MP4863 MP4864 MP5097  E-Stability Checks Calibration 140 Per	
Performed By MH  1017  Iumber SD1014 SD1015 MP4863 MP4864 MP5097 Stability Checks (Calibration n 40 er  L1D-8, FAC chapter 11D-8, FAC	
Perial #: MP4864 Perial #: MP5097  Performed By MH  1017  Dumber SD1014 SD1015 MP4863 MP4864 MP5097  Personal Processor Calibration In 40 Personal Processor Ca	
Performed By MH  1017  Iumber SD1014 SD1015 MP4863 MP4864 MP5097 Stability Checks (Calibration n 40 er  L1D-8, FAC chapter 11D-8, FAC	
it is the second of the second	

## Florida Department of Law Enforcement Alcohol Testing Program

### DEPARTMENT INSPECTION REPORT - INTOXILYZER 8000

Agency: MANATEE COUNTY SO Time of Inspection: 13:51

Standard Deviations

Date of Inspection: 05/08/2020

Serial Number: 80-006236

Software: 8100.27

0.0004

Check or Test	YES	NO	NO Check or Test		ИО
Diagnostic Check			Date and/or Time Adjusted		
(Pre-Inspection): OK	Yes				No
Minimum Sample Volume			Barometric Pressure Sensor		
Check: OK	Yes		Check: OK	Yes	
Alcohol Free Subject			Mouth Alcohol Test:		
Test: 0.000	Yes		Slope Not Met	Yes	
Interferent Detect Test:			Diagnostic Check		
Interferent Detect	Yes		(Post-Inspection): OK Yes		

Alcohol Free Test (g/210L)	0.05g/210L Test (g/210L) Lot#:201905A Exp: 05/14/2021	0.08g/210L Test (g/210L) Lot#:201905B Exp: 05/14/2021	0.20g/210L Test (g/210L) Lot#:201904D Exp: 04/30/2021	0.08 g/210L Dry Gas Std Test (g/210L) Lot#:AG003005 Exp: 01/30/2022
0.000	0.049	0.079	0.199	0.079
0.000	0.050	0.079	0.200	0.080
0.000	0.049	0.080	0.199	0.079
0.000	0.050	0.079	0.200	0.079
0.000	0.050	0.079	0.199	0.079
0.000	0.050	0.080	0.199	0.079
0.000	0.050	0.079	0.200	0.080
0.000	0.050	0.079	0.199	0.079
0.000	0.050	0.079	0.199	0.079
0.000	0.050	0.080	0.199	0.079

Average Standard Deviation of 0.05, 0.08 and 0.20 g/210L Tests: 0.0004 Number of Simulators Used: 5

0.0004

The above instrument complies ( X ) does not comply ( ) with Chapter 11D-8, FAC.

I certafy that I performed this inspection in accordance with the provisions of Chapter 11D-8, FAC.

MICHAEL D HAUGHEY

0.0004

Signature and Printed Name

05/08/2020 Date

FDLE/ATP Form 41 -Revised August 2005

8P 13/2/2020

Operator's Signature	MANATEE COLMT: SS Intoxilyzer - Alcond Atalyzer Model 8800 5: 1-036236 05/08/2022 Software: 8105.27 Test g/2131 Tite Gontrol Test 0.000 Control Test 0.000 Control Test 0.000 Control Test 0.000 Control Test 0.000 Control Test 0.000 Control Test 5.050 Alcondate 0.000 Control Test 5.050 Alcondate 0.000 Control Test 5.050 Alcondate 0.000 Control Test 5.050 Control Test 5.050 Alcondate 0.000 Control Test 5.050 Alcondate 0.000 Control Test 5.050 Control Test 5.05	0.05g/210L 0.047 to 0.053	TYPE OF TEST SERIAL NUM Stabilities 80-006236
Bestim's Cignature	MANATE COUNTY SO Intoxilyzer - 41cohol inalyzer Model 8300 SS/88/2020 Software: 8180.27  Time  Test	0.08g/210L 0.077 to 0.083	SERIAL NUMBER AGENCY 80-006236 Manates County C
Sunsection of the second secon	MANATEE COLNTY SO INTOXINGER - 41conol Analyzer Model 8300 SN 80-535236 S0ftware: 8180.27  Test S0ftware: 8180.27  Test S0ftware: 8180.27  Time Air Blank Control Test Control	0.20g/210L 0.194 to 0.206 [2]	DATE 05/04
W Lightone	MANAGEE TOUR SO INTO JEEN MODEL BIOR SO SOFTWARE: 8105.27  Test 9/2101 The Air Lung Software: 8105.27  Air Blank 0.600 10:31 Control Test 0.600 10:32 Control Test 0.600 10:33 Air Blank 0.600 10:32 Control Test 0.600 10:33 Air Blank 0.600 10:33 Air B	DGS 0.08g/210L 0.077 to 0.083	DATE PERFORMED BY  05/06/2026 /VX

Sp BK 5/28/2020



# **Calibration Certificate**

Florida Department of Law Enforcement Alcohol Testing Program 4700 Terminal Drive, Suite 1 Ft. Myers, FL 33907

FDLE/ATP Form 36 - Department Inspection Procedures - Intoxilyzer 8000. This is to certify the calibration of Intoxilyzer 8000 serial number 80-006236, manufactured by CMI, Inc. was calibrated in accordance with

	Calibration Time:	Calibration Date:	Owning Agency:	Serial Number:
	<u>13:51</u>	05/08/2020	MANATEE COUNTY SO	80-006236
0.080 g/210 L Dry Gas Control	$0.200  \mathrm{g}/210  \mathrm{L}$	0.080  g/210  L	0.050  g/210  L	UNCERTAINTY* ±
0.005	0.007	0.005	0.004	

All results are reported in g/210 L.

Bias is limited by calibration acceptance criteria. All calibration results must be within ± 0.005 or 5%, whichever is greater, of the target alcohol concentration. \*Uncertainty is based on fleet-wide data and is expressed to a 99.73% level of confidence (k=3).

The instrument results before and after any adjustment are found in the associated pre and post stability checks.

## TRACEABILITY INFORMATION

with ISO 17034 and ISO/ IEC 17025 Standards This instrument was calibrated using solutions prepared by Alcohol Countermeasure Systems, Inc. (ACS). ACS prepared and certified these CRMs in accordance

Precision Metrology in accordance with ISO/ IEC 17025 standards. Simulator temperatures are traceable to NIST. Thermometer temperatures are checked with NIST traceable Eutechnics 4400 digital thermometers calibrated by

controls prepared and certified the CRMs in accordance with ISO Guide 34 and ISO/ IEC 17025 standards. This document shall not be reproduced except in full, Dry gas control measurements are traceable to NIST through the uses of CRMs supplied by an accredited CRM supplier. The supplier of dry gas standard

without written approval of the Florida Department of Law Enforcement Alcohol Testing Program.

05/08/2020

Date

MICHAELD HAUGHEY

Department Inspector

FDLE/ATP Form 69 April 2020 Issuing Authority: Alcohol Testing Program

Service • Integrity • Respect • Quality

Page 1 of 1

SP BK 5/28/2020