



INSTRUMENT PROCESSING SHEET

Agency Manatee County SOS/N 80-006559Florida Department of
Law EnforcementDate In 05/01/2020 DI Completion Date 05/05/2020 Ship P/U H/D CMI EE

| Intake Performed By <u>MH</u> <input checked="" type="checkbox"/> Annual <input type="checkbox"/> Registration <input type="checkbox"/> Return from CMI / EE Visual Inspection: <input checked="" type="checkbox"/> Case <input checked="" type="checkbox"/> Handle <input checked="" type="checkbox"/> Keyboard <input checked="" type="checkbox"/> Dry Gas Shelf <input checked="" type="checkbox"/> Feet <input checked="" type="checkbox"/> Breath Tube <input checked="" type="checkbox"/> Ports <input checked="" type="checkbox"/> Screws Tight Other Equipment/ Accessories: <input type="checkbox"/> Power cord <input type="checkbox"/> Printer Cable <input type="checkbox"/> Static Bag <input type="checkbox"/> 12V DC Cable Notes: _____ _____ Final Release Date <div style="text-align: center;">FDLE</div> <div style="text-align: center;">MAY 20 2020</div> <div style="text-align: center;">Alcohol Testing Program</div> | Quality Checks Performed By <u>MH</u> <input checked="" type="checkbox"/> Breath Tube Screen <input checked="" type="checkbox"/> Replace External O-Rings <input checked="" type="checkbox"/> Instrument Set Up Verified <input checked="" type="checkbox"/> R-Value <u>204</u> <input checked="" type="checkbox"/> Flow Verification (L/s) Flow Column # <u>ATP 101</u> 32 mm <u>0.156</u> (.139 - .169) 36 mm <u>0.171</u> (.156 - .190) 53 mm <u>0.246</u> (.228 - .278) 103 mm <u>0.507</u> (.447 - .547) <input checked="" type="checkbox"/> Barometric Pressure Check Gauge ID # <u>28199</u> <input checked="" type="checkbox"/> Stability Checks <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Simulator</th> <th>Serial #</th> <th>Lot #/Exp</th> </tr> </thead> <tbody> <tr> <td>0.050</td> <td rowspan="2">MP4863</td> <td>201905A 05/14/2021</td> </tr> <tr> <td>0.080</td> <td>201905B 05/14/2021</td> </tr> <tr> <td>0.200</td> <td>MP5097</td> <td>201904D 04/30/2021</td> </tr> <tr> <td>0.080 DGS</td> <td>N/A</td> <td>AG931603 11/12/2021</td> </tr> </tbody> </table> | Simulator | Serial # | Lot #/Exp | 0.050 | MP4863 | 201905A 05/14/2021 | 0.080 | 201905B 05/14/2021 | 0.200 | MP5097 | 201904D 04/30/2021 | 0.080 DGS | N/A | AG931603 11/12/2021 | Flow Calibration Performed By _____ Flow Column # _____ <input type="checkbox"/> 5L/min - 17mm <input type="checkbox"/> 15L/min - 53mm <input type="checkbox"/> 30L/min - 103mm <input type="checkbox"/> R-Value _____ <input type="checkbox"/> Post Calibration Verification (L/s) Flow Column # _____ 32 mm _____ (.139 - .169) 36 mm _____ (.156 - .190) 53 mm _____ (.228 - .278) 103 mm _____ (.447 - .547) Maintenance Performed By _____ <input type="checkbox"/> Battery Replacement <input type="checkbox"/> Dry Gas Regulator Replacement <input type="checkbox"/> Breath Tube Replacement <input type="checkbox"/> Other _____ Temperature Checks Performed By <u>MH</u> <input checked="" type="checkbox"/> Lab Temp °C <u>22.78</u> External Digital Therm. ID#: <u>300918</u> <input checked="" type="checkbox"/> 34°C +/- .2 Serial #: <u>MP4863</u> <input checked="" type="checkbox"/> 34°C +/- .2 Serial #: <u>MP4864</u> <input checked="" type="checkbox"/> 34°C +/- .2 Serial #: <u>MP5097</u> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|------------------------|------------|------------|-------|--------|-----------------------|-------|-----------------------|-------|--------|-----------------------|-----------|-----|------------------------|--|-------|--|--|--|-------|--|--|--|-----------|-----|--|--|-----------|---------------|------------|------------|-------|--|--|--|-------|--|--|--|-------|--|--|--|-----------|-----|--|--|---|-----------|---------------|-------|--------|-------------|--------|-------|--------|-------|--------|-------|--------|
| Simulator | Serial # | Lot #/Exp | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.050 | MP4863 | 201905A 05/14/2021 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 | | 201905B 05/14/2021 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.200 | MP5097 | 201904D 04/30/2021 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 DGS | N/A | AG931603 11/12/2021 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Calibration Adjustment Performed By _____ Barometric Pressure Gauge _____ ID # _____ <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Simulator</th> <th>Serial Number</th> <th>Lot Number</th> <th>Expiration</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td></td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>0.040</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.100</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.200</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.300</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.080 DGS</td> <td>N/A</td> <td></td> <td></td> </tr> </tbody> </table> <input type="checkbox"/> Post Calibration Adjustment Stability Checks <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Simulator</th> <th>Serial Number</th> <th>Lot Number</th> <th>Expiration</th> </tr> </thead> <tbody> <tr> <td>0.050</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.080</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.200</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.080 DGS</td> <td>N/A</td> <td></td> <td></td> </tr> </tbody> </table> | Simulator | Serial Number | Lot Number | Expiration | 0.000 | | N/A | N/A | 0.040 | | | | 0.100 | | | | 0.200 | | | | 0.300 | | | | 0.080 DGS | N/A | | | Simulator | Serial Number | Lot Number | Expiration | 0.050 | | | | 0.080 | | | | 0.200 | | | | 0.080 DGS | N/A | | | Department Inspection Performed By <u>MH</u> Barometric Pressure ID# <u>28663</u> Gauge <u>1016</u> Instrument <u>1009</u> Mouth Alcohol Solution Lot # <u>2019-A</u> Acetone Stock Solution Lot # <u>2019-B</u> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Simulator</th> <th>Serial Number</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td>SD1014</td> </tr> <tr> <td>Interferent</td> <td>SD1015</td> </tr> <tr> <td>0.050</td> <td>MP4863</td> </tr> <tr> <td>0.080</td> <td>MP4864</td> </tr> <tr> <td>0.200</td> <td>MP5097</td> </tr> </tbody> </table> Attachments <input checked="" type="checkbox"/> Form 41 <input type="checkbox"/> Post-Stability Checks <input checked="" type="checkbox"/> Stability Checks <input type="checkbox"/> Flow Calibration <input checked="" type="checkbox"/> Calibration Certificate <input type="checkbox"/> Form 40 <input type="checkbox"/> Calibration Adjustment <input type="checkbox"/> Other _____ | Simulator | Serial Number | 0.000 | SD1014 | Interferent | SD1015 | 0.050 | MP4863 | 0.080 | MP4864 | 0.200 | MP5097 |
| Simulator | Serial Number | Lot Number | Expiration | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.000 | | N/A | N/A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.040 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.100 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.300 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 DGS | N/A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Simulator | Serial Number | Lot Number | Expiration | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.050 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 DGS | N/A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Simulator | Serial Number | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.000 | SD1014 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Interferent | SD1015 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.050 | MP4863 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 | MP4864 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.200 | MP5097 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Notes/Suggested Service: <u>E-mailed</u> <div style="border: 1px solid blue; padding: 5px; display: inline-block; color: blue;"> <input checked="" type="checkbox"/> APPROVED 05/08/2020 </div> | <input checked="" type="checkbox"/> Instrument Complies with Chapter 11D-8, FAC <input type="checkbox"/> Instrument Does Not Comply with Chapter 11D-8, FAC <input checked="" type="checkbox"/> Return to/Place into Evidentiary Use <input type="checkbox"/> Remain Out of Evidentiary Use <input checked="" type="checkbox"/> Conduct an Agency Inspection Before Evidentiary Use <div style="text-align: center; margin-top: 10px;"> <u>SR 5/15/20</u> <u>Brett Kirkland 5/18/2020</u> Tech Review / Date Admin Review / Date </div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Florida Department of Law Enforcement Alcohol Testing Program

DEPARTMENT INSPECTION REPORT - INTOXILYZER 8000

Agency: MANATEE COUNTY SO
Time of Inspection: 12:30

Date of Inspection: 05/05/2020

Serial Number: 80-006559
Software: 8100.27

| Check or Test | YES | NO | Check or Test | YES | NO |
|---|-----|----|--|-----|----|
| Diagnostic Check (Pre-Inspection): OK | Yes | | Date and/or Time Adjusted | | No |
| Minimum Sample Volume Check: OK | Yes | | Barometric Pressure Sensor Check: OK | Yes | |
| Alcohol Free Subject Test: 0.000 | Yes | | Mouth Alcohol Test: Slope Not Met | Yes | |
| Interferent Detect Test: Interferent Detect | Yes | | Diagnostic Check (Post-Inspection): OK | Yes | |

| Alcohol Free Test (g/210L) | 0.05g/210L Test (g/210L) Lot#:201905A Exp: 05/14/2021 | 0.08g/210L Test (g/210L) Lot#:201905B Exp: 05/14/2021 | 0.20g/210L Test (g/210L) Lot#:201904D Exp: 04/30/2021 | 0.08 g/210L Dry Gas Std Test (g/210L) Lot#:AG931603 Exp: 11/12/2021 |
|----------------------------|---|---|---|---|
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |

| | | | | |
|---------------------|--------|--------|--------|--------|
| Standard Deviations | 0.0000 | 0.0000 | 0.0000 | 0.0000 |
|---------------------|--------|--------|--------|--------|


Average Standard Deviation of 0.05, 0.08 and 0.20 g/210L Tests: 0.0000 Number of Simulators Used: 5

Remarks:

SP
JSLK
5/18/2020

The above instrument complies () does not comply () with Chapter 11D-8, FAC.

I certify that I performed this inspection in accordance with the provisions of Chapter 11D-8, FAC.



MICHAEL D HAUGHEY

Signature and Printed Name

05/05/2020
Date

| TYPE OF TEST | SERIAL NUMBER | AGENCY | DATE | PERFORMED BY |
|--------------|---------------|-------------------|------------|--------------|
| Stabilities | 80-006559 | Manatee County SO | 05/05/2020 | MA |

0.05g/210L
0.047 to 0.053

0.08g/210L
0.077 to 0.083

0.20g/210L
0.194 to 0.206

DGS 0.08g/210L
0.077 to 0.083

MANATEE COUNTY SO
Intoxilyzer - Alcohol Analyzer
Model 8000
05/05/2020
SN 80-006559
Software: 8100.27

MANATEE COUNTY SO
Intoxilyzer - Alcohol Analyzer
Model 8000
05/05/2020
SN 80-006559
Software: 8100.27

MANATEE COUNTY SO
Intoxilyzer - Alcohol Analyzer
Model 8000
05/05/2020
SN 80-006559
Software: 8100.27

MANATEE COUNTY SO
Intoxilyzer - Alcohol Analyzer
Model 8000
05/05/2020
SN 80-006559
Software: 8100.27

g/210L

| Test | g/210L | Time |
|----------------|--------|-------|
| Air Blank | 0.000 | 09:31 |
| Control Test | 0.049 | 09:32 |
| Air Blank | 0.000 | 09:32 |
| Control Test | 0.049 | 09:32 |
| Air Blank | 0.000 | 09:33 |
| Control Test | 0.049 | 09:33 |
| Air Blank | 0.000 | 09:34 |
| Control Test | 0.000 | 09:34 |
| Average | 0.0490 | |
| Std Dev | 0.0000 | |
| Rel Std Dev(%) | 0.0000 | |

g/210L

| Test | g/210L | Time |
|----------------|--------|-------|
| Air Blank | 0.000 | 09:37 |
| Control Test | 0.079 | 09:38 |
| Air Blank | 0.000 | 09:38 |
| Control Test | 0.080 | 09:39 |
| Air Blank | 0.000 | 09:39 |
| Control Test | 0.079 | 09:40 |
| Air Blank | 0.000 | 09:40 |
| Control Test | 0.000 | 09:40 |
| Average | 0.0793 | |
| Std Dev | 0.0006 | |
| Rel Std Dev(%) | 0.7277 | |

g/210L

| Test | g/210L | Time |
|----------------|--------|-------|
| Air Blank | 0.000 | 09:43 |
| Control Test | 0.200 | 09:44 |
| Air Blank | 0.000 | 09:44 |
| Control Test | 0.200 | 09:44 |
| Air Blank | 0.000 | 09:45 |
| Control Test | 0.200 | 09:45 |
| Air Blank | 0.000 | 09:45 |
| Control Test | 0.200 | 09:45 |
| Air Blank | 0.000 | 09:46 |
| Control Test | 0.000 | 09:46 |
| Average | 0.2000 | |
| Std Dev | 0.0000 | |
| Rel Std Dev(%) | 0.0000 | |

g/210L

| Test | g/210L | Time |
|----------------|--------|-------|
| Air Blank | 0.000 | 09:49 |
| Control Test | 0.080 | 09:50 |
| Air Blank | 0.000 | 09:50 |
| Control Test | 0.080 | 09:50 |
| Air Blank | 0.000 | 09:51 |
| Control Test | 0.080 | 09:51 |
| Air Blank | 0.000 | 09:52 |
| Control Test | 0.000 | 09:52 |
| Average | 0.0800 | |
| Std Dev | 0.0000 | |
| Rel Std Dev(%) | 0.0000 | |


MAK
Operator's Signature

MAK
Operator's Signature

MAK
Operator's Signature

MAK
Operator's Signature

SP
YBK
5/19/2020



Calibration Certificate

Florida Department of Law Enforcement
Alcohol Testing Program
4700 Terminal Drive, Suite 1
Ft. Myers, FL 33907

This is to certify the calibration of Intoxilyzer 8000 serial number 80-006559, manufactured by CML, Inc. was calibrated in accordance with FDLE/ATP Form 36 - Department Inspection Procedures - Intoxilyzer 8000.

| | | | |
|-------------------|--------------------------|--------------------------------|-------|
| Serial Number: | <u>80-006559</u> | UNCERTAINTY* ± | |
| Owning Agency: | <u>MANATEE COUNTY SO</u> | 0.050 g/ 210 L | 0.004 |
| Calibration Date: | <u>05/05/2020</u> | 0.080 g/ 210 L | 0.005 |
| Calibration Time: | <u>12:30</u> | 0.200 g/ 210 L | 0.007 |
| | | 0.080 g/ 210 L Dry Gas Control | 0.005 |

All results are reported in g/ 210 L.
Bias is limited by calibration acceptance criteria. All calibration results must be within ± 0.005 or 5%, whichever is greater, of the target alcohol concentration.
*Uncertainty is based on fleet-wide data and is expressed to a 99.73% level of confidence (k=3).
The instrument results before and after any adjustment are found in the associated pre and post stability checks.

TRACEABILITY INFORMATION
This instrument was calibrated using solutions prepared by Alcohol Countermeasure Systems, Inc. (ACS). ACS prepared and certified these CRMs in accordance with ISO 17034 and ISO/ IEC 17025 Standards.

Simulator temperatures are traceable to NIST. Thermometer temperatures are checked with NIST traceable Eutechnics 4400 digital thermometers calibrated by Precision Metrology in accordance with ISO/ IEC 17025 standards.

Dry gas control measurements are traceable to NIST through the uses of CRMs supplied by an accredited CRM supplier. The supplier of dry gas standard controls prepared and certified the CRMs in accordance with ISO Guide 34 and ISO/ IEC 17025 standards.
This document shall not be reproduced except in full, without written approval of the Florida Department of Law Enforcement Alcohol Testing Program.

Date 05/05/2020
Michael D Haughey
MICHAEL D HAUGHEY,
Department Inspector

Handwritten notes: 159, BK, 5/22/2020, MK



INSTRUMENT PROCESSING SHEET

Agency Manatee County SO

S/N 80-006559

Florida Department of Law Enforcement

Date In 05/01/2020 DI Completion Date 05/05/2020

Ship P/U H/D CMI EE

| Intake Performed By <u>MH</u> <input checked="" type="checkbox"/> Annual <input type="checkbox"/> Registration <input type="checkbox"/> Return from CMI / EE Visual Inspection: <input checked="" type="checkbox"/> Case <input checked="" type="checkbox"/> Handle <input checked="" type="checkbox"/> Keyboard <input checked="" type="checkbox"/> Dry Gas Shelf <input checked="" type="checkbox"/> Feet <input checked="" type="checkbox"/> Breath Tube <input checked="" type="checkbox"/> Ports <input checked="" type="checkbox"/> Screws Tight Other Equipment/ Accessories: <input type="checkbox"/> Power cord <input type="checkbox"/> Printer Cable <input type="checkbox"/> Static Bag <input type="checkbox"/> 12V DC Cable Notes: _____ _____ Final Release Date <div style="text-align: center;"> FDLE MAY 20 2020 Alcohol Testing Program </div> | Quality Checks Performed By <u>MH</u> <input checked="" type="checkbox"/> Breath Tube Screen <input checked="" type="checkbox"/> Replace External O-Rings <input checked="" type="checkbox"/> Instrument Set Up Verified <input checked="" type="checkbox"/> R-Value <u>204</u> <input checked="" type="checkbox"/> Flow Verification (L/s) Flow Column # <u>ATP 101</u> 32 mm <u>0.156</u> (.139 - .169) 36 mm <u>0.171</u> (.156 - .190) 53 mm <u>0.246</u> (.228 - .278) 103 mm <u>0.507</u> (.447 - .547) <input checked="" type="checkbox"/> Barometric Pressure Check Gauge ID # <u>28199</u> <input checked="" type="checkbox"/> Stability Checks <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Simulator</th> <th>Serial #</th> <th>Lot #/Exp</th> </tr> </thead> <tbody> <tr> <td>0.050</td> <td rowspan="2">MP4863</td> <td>201905A 05/14/2021</td> </tr> <tr> <td>0.080</td> <td>201905B 05/14/2021</td> </tr> <tr> <td>0.200</td> <td>MP5097</td> <td>201904D 04/30/2021</td> </tr> <tr> <td>0.080 DGS</td> <td>N/A</td> <td>AG931603 11/12/2021</td> </tr> </tbody> </table> | Simulator | Serial # | Lot #/Exp | 0.050 | MP4863 | 201905A 05/14/2021 | 0.080 | 201905B 05/14/2021 | 0.200 | MP5097 | 201904D 04/30/2021 | 0.080 DGS | N/A | AG931603 11/12/2021 | Flow Calibration Performed By _____ Flow Column # _____ <input type="checkbox"/> 5L/min - 17mm <input type="checkbox"/> 15L/min - 53mm <input type="checkbox"/> 30L/min - 103mm <input type="checkbox"/> R-Value _____ <input type="checkbox"/> Post Calibration Verification (L/s) Flow Column # _____ 32 mm _____ (.139 - .169) 36 mm _____ (.156 - .190) 53 mm _____ (.228 - .278) 103 mm _____ (.447 - .547) Maintenance Performed By _____ <input type="checkbox"/> Battery Replacement <input type="checkbox"/> Dry Gas Regulator Replacement <input type="checkbox"/> Breath Tube Replacement <input type="checkbox"/> Other _____ Temperature Checks Performed By <u>MH</u> <input checked="" type="checkbox"/> Lab Temp °C <u>22.78</u> External Digital Therm. ID#: <u>300918</u> <input checked="" type="checkbox"/> 34°C +/-2 Serial #: <u>MP4863</u> <input checked="" type="checkbox"/> 34°C +/-2 Serial #: <u>MP4864</u> <input checked="" type="checkbox"/> 34°C +/-2 Serial #: <u>MP5097</u> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|------------------------|------------|------------|-------|--------|-----------------------|-------|-----------------------|-------|--------|-----------------------|-----------|-----|------------------------|--|-------|--|--|--|-------|--|--|--|-----------|-----|--|--|-----------|---------------|------------|------------|-------|--|--|--|-------|--|--|--|-------|--|--|--|-----------|-----|--|--|---|-----------|---------------|-------|--------|-------------|--------|-------|--------|-------|--------|-------|--------|
| Simulator | Serial # | Lot #/Exp | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.050 | MP4863 | 201905A 05/14/2021 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 | | 201905B 05/14/2021 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.200 | MP5097 | 201904D 04/30/2021 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 DGS | N/A | AG931603 11/12/2021 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Calibration Adjustment Performed By _____ Barometric Pressure Gauge _____ ID # _____ <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Simulator</th> <th>Serial Number</th> <th>Lot Number</th> <th>Expiration</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td></td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>0.040</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.100</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.200</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.300</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.080 DGS</td> <td>N/A</td> <td></td> <td></td> </tr> </tbody> </table> <input type="checkbox"/> Post Calibration Adjustment Stability Checks <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Simulator</th> <th>Serial Number</th> <th>Lot Number</th> <th>Expiration</th> </tr> </thead> <tbody> <tr> <td>0.050</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.080</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.200</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.080 DGS</td> <td>N/A</td> <td></td> <td></td> </tr> </tbody> </table> | Simulator | Serial Number | Lot Number | Expiration | 0.000 | | N/A | N/A | 0.040 | | | | 0.100 | | | | 0.200 | | | | 0.300 | | | | 0.080 DGS | N/A | | | Simulator | Serial Number | Lot Number | Expiration | 0.050 | | | | 0.080 | | | | 0.200 | | | | 0.080 DGS | N/A | | | Department Inspection Performed By <u>MH</u> Barometric Pressure ID# <u>28663</u> Gauge <u>1016</u> Instrument <u>1009</u> Mouth Alcohol Solution Lot # <u>2019-A</u> Acetone Stock Solution Lot # <u>2019-B</u> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Simulator</th> <th>Serial Number</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td>SD1014</td> </tr> <tr> <td>Interferent</td> <td>SD1015</td> </tr> <tr> <td>0.050</td> <td>MP4863</td> </tr> <tr> <td>0.080</td> <td>MP4864</td> </tr> <tr> <td>0.200</td> <td>MP5097</td> </tr> </tbody> </table> Attachments <input checked="" type="checkbox"/> Form 41 <input type="checkbox"/> Post-Stability Checks <input checked="" type="checkbox"/> Stability Checks <input type="checkbox"/> Flow Calibration <input checked="" type="checkbox"/> Calibration Certificate <input type="checkbox"/> Form 40 <input type="checkbox"/> Calibration Adjustment <input type="checkbox"/> Other _____ | Simulator | Serial Number | 0.000 | SD1014 | Interferent | SD1015 | 0.050 | MP4863 | 0.080 | MP4864 | 0.200 | MP5097 |
| Simulator | Serial Number | Lot Number | Expiration | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.000 | | N/A | N/A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.040 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.100 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.300 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 DGS | N/A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Simulator | Serial Number | Lot Number | Expiration | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.050 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 DGS | N/A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Simulator | Serial Number | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.000 | SD1014 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Interferent | SD1015 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.050 | MP4863 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 | MP4864 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.200 | MP5097 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Notes/Suggested Service: <u>E-mailed</u> <div style="border: 1px solid black; padding: 5px; display: inline-block;"> <input checked="" type="checkbox"/> APPROVED <u>05/08/2020</u> </div> | <input checked="" type="checkbox"/> Instrument Complies with Chapter 11D-8, FAC <input type="checkbox"/> Instrument Does Not Comply with Chapter 11D-8, FAC <input checked="" type="checkbox"/> Return to/Place into Evidentiary Use <input type="checkbox"/> Remain Out of Evidentiary Use <input checked="" type="checkbox"/> Conduct an Agency Inspection Before Evidentiary Use <div style="text-align: center; margin-top: 10px;"> <u>SR 5/15/20</u> <u>Scott Kirkland 5/18/2020</u> Tech Review / Date Admin Review / Date </div> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Florida Department of Law Enforcement Alcohol Testing Program

DEPARTMENT INSPECTION REPORT - INTOXILYZER 8000

Agency: MANATEE COUNTY SO
Time of Inspection: 12:30

Date of Inspection: 05/05/2020

Serial Number: 80-006559
Software: 8100.27

| Check or Test | YES | NO | Check or Test | YES | NO |
|---|-----|----|--|-----|----|
| Diagnostic Check (Pre-Inspection): OK | Yes | | Date and/or Time Adjusted | | No |
| Minimum Sample Volume Check: OK | Yes | | Barometric Pressure Sensor Check: OK | Yes | |
| Alcohol Free Subject Test: 0.000 | Yes | | Mouth Alcohol Test: Slope Not Met | Yes | |
| Interferent Detect Test: Interferent Detect | Yes | | Diagnostic Check (Post-Inspection): OK | Yes | |

| Alcohol Free Test (g/210L) | 0.05g/210L Test (g/210L) Lot#:201905A Exp: 05/14/2021 | 0.08g/210L Test (g/210L) Lot#:201905B Exp: 05/14/2021 | 0.20g/210L Test (g/210L) Lot#:201904D Exp: 04/30/2021 | 0.08 g/210L Dry Gas Std Test (g/210L) Lot#:AG931603 Exp: 11/12/2021 |
|----------------------------|---|---|---|---|
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |
| 0.000 | 0.049 | 0.079 | 0.200 | 0.080 |

| | | | | |
|---------------------|--------|--------|--------|--------|
| Standard Deviations | 0.0000 | 0.0000 | 0.0000 | 0.0000 |
|---------------------|--------|--------|--------|--------|


Average Standard Deviation of 0.05, 0.08 and 0.20 g/210L Tests: 0.0000 Number of Simulators Used: 5

Remarks:

SP
YBK
5/18/2020

The above instrument complies () does not comply () with Chapter 11D-8, FAC.

I certify that I performed this inspection in accordance with the provisions of Chapter 11D-8, FAC.



MICHAEL D HAUGHEY

Signature and Printed Name

05/05/2020
Date

| TYPE OF TEST | SERIAL NUMBER | AGENCY | DATE | PERFORMED BY |
|--------------|---------------|-------------------|------------|--------------|
| Stabilites | 80-006559 | Manatee County SO | 05/05/2020 | MA |

0.05g/210L

0.08g/210L

0.20g/210L

DGS 0.08g/210L

MANATEE COUNTY SO
Intoxilizer - Alcohol Analyzer
Model 8000
05/05/2020
SN 80-006559
Software: 8100.27

MANATEE COUNTY SO
Intoxilizer - Alcohol Analyzer
Model 8000
05/05/2020
SN 80-006559
Software: 8100.27

MANATEE COUNTY SO
Intoxilizer - Alcohol Analyzer
Model 8000
05/05/2020
SN 80-006559
Software: 8100.27

MANATEE COUNTY SO
Intoxilizer - Alcohol Analyzer
Model 8000
05/05/2020
SN 80-006559
Software: 8100.27

Test g/210L Time

Air Blank 0.000 09:31
Control Test 0.049 09:32
Air Blank 0.000 09:32
Control Test 0.049 09:32
Air Blank 0.000 09:33
Control Test 0.049 09:33
Air Blank 0.000 09:34
Control Test 0.000 09:34

Average 0.0490
Std Dev 0.0000
Rel Std Dev(%) 0.0000

Test g/210L Time

Air Blank 0.000 09:37
Control Test 0.079 09:38
Air Blank 0.000 09:38
Control Test 0.080 09:38
Air Blank 0.000 09:39
Control Test 0.079 09:39
Air Blank 0.000 09:40
Control Test 0.000 09:40

Average 0.0793
Std Dev 0.0006
Rel Std Dev(%) 0.7277

Test g/210L Time

Air Blank 0.000 09:43
Control Test 0.200 09:44
Air Blank 0.000 09:44
Control Test 0.200 09:44
Air Blank 0.000 09:45
Control Test 0.000 09:45
Air Blank 0.200 09:46
Control Test 0.000 09:47

Average 0.2000
Std Dev 0.0000
Rel Std Dev(%) 0.0000

Test g/210L Time

Air Blank 0.000 09:49
Control Test 0.080 09:50
Air Blank 0.000 09:50
Control Test 0.080 09:50
Air Blank 0.000 09:51
Control Test 0.080 09:51
Air Blank 0.000 09:52

Average 0.0800
Std Dev 0.0000
Rel Std Dev(%) 0.0000


MA
Operator's Signature

MA
Operator's Signature

MA
Operator's Signature

MA
Operator's Signature

SP
YBK
5/18/2020



Calibration Certificate

Florida Department of Law Enforcement
Alcohol Testing Program
4700 Terminal Drive, Suite 1
Ft. Myers, FL 33907

This is to certify the calibration of Intoxilyzer 8000 serial number 80-006559, manufactured by CMI, Inc. was calibrated in accordance with FDLE/ATP Form 36 - Department Inspection Procedures - Intoxilyzer 8000.

| | | |
|-------------------|--------------------------|--|
| Serial Number: | <u>80-006559</u> | UNCERTAINTY* ± |
| Owning Agency: | <u>MANATEE COUNTY SO</u> | 0.050 g/210 L 0.004 |
| Calibration Date: | <u>05/05/2020</u> | 0.080 g/210 L 0.005 |
| Calibration Time: | <u>12:30</u> | 0.200 g/210 L 0.007 |
| | | 0.080 g/210 L Dry Gas Control 0.005 |

All results are reported in g/210 L.
Bias is limited by calibration acceptance criteria. All calibration results must be within ± 0.005 or 5%, whichever is greater, of the target alcohol concentration.
*Uncertainty is based on fleet-wide data and is expressed to a 99.73% level of confidence (k=3).
The instrument results before and after any adjustment are found in the associated pre and post stability checks.

TRACEABILITY INFORMATION
This instrument was calibrated using solutions prepared by Alcohol Countermeasure Systems, Inc. (ACS). ACS prepared and certified these CRMs in accordance with ISO 17034 and ISO/IEC 17025 Standards.

Simulator temperatures are traceable to NIST. Thermometer temperatures are checked with NIST traceable Eutechnics 4400 digital thermometers calibrated by Precision Metrology in accordance with ISO/IEC 17025 standards.

Dry gas control measurements are traceable to NIST through the uses of CRMs supplied by an accredited CRM supplier. The supplier of dry gas standard controls prepared and certified the CRMs in accordance with ISO Guide 34 and ISO/IEC 17025 standards.
This document shall not be reproduced except in full, without written approval of the Florida Department of Law Enforcement Alcohol Testing Program.

Date 05/05/2020
Michael D. Haughey
MICHAEL D HAUGHEY,
Department Inspector

ISD
B/K
5/28/2020