

### **INSTRUMENT PROCESSING SHEET**

Agency Florida Highway Patrol S/N 80-000782

Florida Department of Law Enforcement

Date In <u>01-26-2023</u> DI Completion Date <u>01-26-2023</u> □Ship ■P/U □H/D □CMI □EE

Intake By IS	Q	uality Che	cks By <u>IS</u>	Date_01-26-2023	Flow Calibr	ation By	Date
■ Annual		Breath Tu	ıbe Screen		Flow Colum	nn #	
☐ Registration		Replace External O-Rin		gs	<b>□</b> 5L/r	nin – 17mm	
☐ Return from CMI / EE		Instrume	nt Set Up Verif	fied	☐ 15L,	/min – 53mm	
Viewel Incorporation.		R-Value _	194		☐ 30L,	/min – 103mm	
Visual Inspection:		Flow Veri	fication (L/s)		☐ R-Value		
■ Case ■ Handle	FI/		n # ATP-105			bration Verificat	 ion (L/s)
Keyboard Dry Gas She	eit			(.139169)		nn #	
Feet Breath Tub	e			(.156190)	32 mm		
Ports Screws Tigh					36 mm		(156 - 190)
Other Equipment/ Accessories:	1	53 mm <u>0.250</u> 103 mm <u>0.531</u>		(.220270)			
☐ Power cord ☐ Printer Cab			ric Pressure Ch				
☐ Static Bag ☐ 12V DC Cab	.   -			еск	103 111111 _		(.447547)
	00	Gauge ID # <u>30793</u>					
Notes:		Stability (					
	Si	Simulator	Serial #	Lot #/Exp	Maintenan		Ву
	<u> </u>	0.050	MDCCOA	202201C		Replacement	
			MP6291	01-11-2024	-	Regulator Replac	
	O	0.080	MPOOOO	202201D		ube Replacemen	t
			MP6292	01-18-2024	Other		
	l o	).200		202201E			
	-		MP6293	01-18-2024			
		0.080 DGS	N/A	AG113403			
	0	7.060 DG3	IN/A	05-14-2023			
C-libration Adirectors and			Des		••		p. 19
Calibration Adjustment			By	Department Inspec			By IS
Barometric Pressure Gauge		ID#		Barometric Pressure Gauge 1019			
Simulator Serial #	Lot #			•	-		
0.000	N/A	4	N/A	Mouth Alcohol Solu			
0.040				Acetone Stock Solut	ion Lot # <u>20</u>		
0.100				Simulator		Serial Number	200
0.200				0.000 Interferent		MP62	
0.300				0.050		MP62 MP62	
0.080 DGS N/A				0.080		MP62	
				0.200		MP62	
□ Post Calibration Adjustment				Attachus sute	<u>.</u>		
Simulator   Serial #	Lot #	E	xpiration	Attachments			
0.050				Form 41		☐ Post-Stability	
0.080				Stability Checks		☐ Flow Calibrat	tion
0.200				Calibration Cert		☐ Form 40	
0.080 DGS N/A				☐ Calibration Adju	ıstment	Other	
Notes/Suggested Service: Instrument Complies with Chapter 11D-8, FAC							
Notes/Suggested Service:			☐ Instrument Compiles with Chapter 11D-8, FAC				
			■ Return to/Place into Evidentiary Use □ Remain Out of Evidentiary Use				
-				etion. He -			
Conduct an Agency Inspection Before Evidentiary Use					ntiary Use		
				Taylor Gutschow  Digitally signed by Taylor Gutschow  Digitally signed by Phil Nicodemo Date: 2023.01.2615:1831  Openion  Digitally signed by Phil Nicodemo Date: 2023.01.31 11:04:53 -05'00'			
				Tech Review / Da	ite	Admin Review	/ Date

# Florida Department of Law Enforcement Alcohol Testing Program

# DEPARTMENT INSPECTION REPORT - INTOXILYZER 8000

Agency: FHP

Time of Inspection: 13:27

Date of Inspection: 01/26/2023

Serial Number: 80-000782

Software: 8100.27

Check or Test	YES	NO	Check or Test	YES	NO
Diagnostic Check (Pre-Inspection): OK	Yes		Date and/or Time Adjusted		No
Minimum Sample Volume Check: OK	Yes		Barometric Pressure Sensor Check: OK	Yes	
Alcohol Free Subject Test: 0.000	Yes		Mouth Alcohol Test: Slope Not Met	Yes	
Interferent Detect Test: Interferent Detect	Yes		Diagnostic Check (Post-Inspection): OK	Yes	

Alcohol Free Test (g/210L)	0.05g/210L Test (g/210L) Lot#:202201C Exp: 01/11/2024	0.08g/210L Test (g/210L) Lot#:202201D Exp: 01/18/2024	0.20g/210L Test (g/210L) Lot#:202201E Exp: 01/18/2024	0.08 g/210L Dry Gas Std Test (g/210L) Lot#:AG229803 Exp: 10/25/2024
0.000	0.050	0.079	0.201	0.082
0.000	0.050	0.080	0.202	0.082
0.000	0.050	0.080	0.202	0.082
0.000	0.050	0.080	0.202	0.082
0.000	0.050	0.080	0.202	0.081
0.000	0.050	0.080	0.202	0.082
0.000	0.050	0.080	0.202	0.082
0.000	0.050	0.080	0.202	0.082
0.000	0.051	0.080	0.202	0.082
0.000	0.051	0.081	0.202	0.081
Standard Deviations	0.0004	0.0004	0.0003	0.0004

Average Standard Deviation of 0.05, 0.08 and 0.20 g/210L Tests: 0.0003 Number of Simulators Used: 5

The above instrument complies ( X ) does not comply ( ) with Chapter 11D-8, FAC.

I certify that I performed this inspection in accordance with the provisions of Chapter 11D-8, FAC.

ISRAEL SOTO Signature and Printed Name

01/26/2023 Date

# stability checks

FHP
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-000782
01/26/2023
Software: 8100.27

Test	g/210L	Time
Air Blank Control Test Air Blank Control Test Air Blank Control Test Air Blank Control Test	0.000 0.050 0.000 0.050 0.050 0.050	11:34 11:35 11:36 11:36 11:37 11:38
Control Test Stat Average Std Dev Rel Std Dev(%)	0.0500 0.0000 0.0000	

S.

Operator's Signature

FHP
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-000782
01/26/2023
Software: 8100.27

Test	g/210L	Time
Air Blank Control Test Air Blank Control Test Air Blank Control Test Air Blank	0.000 0.080 0.000 0.000 0.000 0.000	11:39 11:40 11:41 11:41 11:42 11:43
Control Test Sta Average Std Dev Rel Std Dev(%)	ts 0.0800 0.0000	11:45

wet

Operator's Signature

FHP
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-000782
01/26/2023
Software: 8100.27

Test	g/210L	Time
Air Blank Control Test Air Blank Control Test Air Blank Control Test Air Blank Control Test		11: 44 11: 45 11: 46 11: 46 11: 48 11: 48
Average Std Dev Rel Std Dev(	0.2010 0.0000 (%) 0.0000	

Operator's Signature

FHP
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-000782
01/26/2023
Software: 8100.27

Test	g/210L	Time
Air Blank Control Test Staty	0.000 0.082 0.000 0.083 0.000 0.082 0.000	11:49 11:49 11:50 11:51 11:51 11:51
Average Std Dev Re! Std Dev(%)	0.0823 0.0006	

Dry

Operator's Signature



## **Calibration Certificate**

Florida Department of Law Enforcement Alcohol Testing Program 2331 Phillips Road. Suite B1032 Tallahassee, FL 32308

This is to certify the calibration of Intoxilyzer 8000 serial number 80-000782, manufactured by CMI, Inc. was calibrated in accordance with FDLE/ATP Form 36 - Department Inspection Procedures - Intoxilyzer 8000.

Serial Number:	80-000782	UNCERTAINTY* ±	
Owning Agency:	FHP WENT OF	0.050 g/ 210 L	0.004
Calibration Date:	01/26/2023	0.080 g/ <mark>21</mark> 0 L	0.004
Calibration Time:	13:27	0.200 g/ 210 L	0.007
		0.080 g/210 L Dry Gas Control	0.005

All results are reported in g/210 L.

Bias is limited by calibration acceptance criteria. All calibration results must be within ± 0.005 or 5%, whichever is greater, of the target alcohol concentration. \*Uncertainty is based on fleet-wide data and is expressed to a 99.73% level of confidence (k=3).

The instrument results before and after any adjustment are found in the associated pre and post stability checks.

#### TRACEABILITY INFORMATION

This instrument was calibrated using solutions prepared by Alcohol Countermeasure Systems, Inc. (ACS). ACS prepared and certified these CRMs in accordance with ISO 17034 and ISO/IEC 17025 Standards.

Simulator temperatures are traceable to NIST. Simulator temperatures are checked with NIST traceable digital thermometers calibrated by Precision Metrology in accordance with ISO/ IEC 17025 standards.

Dry gas control measurements are traceable to NIST through the use of CRMs supplied by an accredited CRM supplier. The supplier of dry gas standard controls prepared and certified the CRMs in accordance with ISO Guide 34 and ISO/IEC 17025 standards. Digitally signed by Israel

This document shall not be reproduced except in full, without written approval of the Florida Department of Law Enforcement Alcohol Testing Program.

01/26/2023

Israel Soto Soto Date: 2023.01.26 14:46:55

-05'00'

Date

ISRAEL SOTO, Department Inspector

FDLE/ATP Form 69 March 2022

Issuing Authority: Alcohol Testing Program

Service • Integrity • Respect • Quality

Page 1 of 1