

INSTRUMENT PROCESSING SHEET

Agency FDLE s/n 80-000219 Florida Department of Date In 12-11-2020 DI Completion Date 12-14-2020 Ship P/U H/D CMI DEE Law Enforcement Performed By IS Intake **Quality Checks** Performed By IS Flow Calibration Performed By Annual Breath Tube Screen Flow Column # ☐ Registration ☑ Replace External O-Rings ☐ 5L/min - 17mm ☐ Return from CMI / EE Instrument Set Up Verified ☐ 15L/min – 53mm ☑ R-Value 219 ☐ 30L/min – 103mm Visual Inspection: Flow Verification (L/s) Case Handle Flow Column # ATP-105 ☐ Post Calibration Verification (L/s) Keyboard Dry Gas Shelf 32 mm 0.160 Flow Column #_____ (.139 - .169) **☑** Feet ☑ Breath Tube 36 mm 0.171 __(.156 - .190) 32 mm _____(.139 - .169) 2 Ports Screws Tight 53 mm 0.250 (.228 - .278) 36 mm _____ (.156 - .190) Other Equipment/ Accessories: 103 mm 0.531 (.447 - .547) 53 mm _____ (.228 - .278) ☐ Power cord ☐ Printer Cable Barometric Pressure Check 103 mm _____(.447 - .547) ✓ Static Bag ☐ 12V DC Cable Gauge ID # 30793 Stability Checks Maintenance Performed By Notes: ____ Simulator ☐ Battery Replacement Serial # Lot #/Exp ☐ Dry Gas Regulator Replacement 0.050 201905A MP5088 ☐ Breath Tube Replacement 05-14-2021 Other **Final Release Date** 0.080 202010B MP5086 Temperature Checks Performed By IS **FDLE** 10-05-2022 Digitally signed ✓ Lab Temp °C 21.35 0.200 201904D by FDLE Alcohol Alcohol External Digital Therm. ID#: 300505 MP5090 04-30-2021 Testing Program 2 34°C +-.2 Serial #: MP5088 **Testing** 0.080 DGS N/A AG011102 Date: 2020.12.16 2 34°C +-.2 Serial #: MP5086 00:37:50 -05'00' 04-20-2022 **☑** 34°C +-.2 Serial #: MP5090 **Program Calibration Adjustment** Performed By Performed By IS **Department Inspection** Barometric Pressure Gauge Barometric Pressure ID# 30793 ID# Simulator Serial Number Lot Number Expiration Gauge 1013 Instrument 1012 0.000 Mouth Alcohol Solution Lot # 2020-A N/A N/A Acetone Stock Solution Lot # 2019-A 0.040 Simulator Serial Number 0.100 0.000 G11621 0.200 Interferent MP5087 0.300 0.050 MP5088 0.080 DGS N/A 0.080 MP5086 ☐ Post Calibration Adjustment Stability Checks 0.200 MP5090 Simulator Serial Number Lot Number Expiration **Attachments** 0.050 **☑** Form 41 ☐ Post-Stability Checks 0.080 Stability Checks ☐ Flow Calibration 0.200 ☑ Calibration Certificate ☐ Form 40 ☐ Calibration Adjustment ☐ Other 0.080 DGS N/A Notes/Suggested Service: _____ Instrument Complies with Chapter 11D-8, FAC ☐ Instrument Does Not Comply with Chapter 11D-8, FAC ☑ Return to/Place into Evidentiary Use ☐ Remain Out of Evidentiary Use Conduct an Agency Inspection Before Evidentiary Use 2020.12.1 Model D. Haughey 09:30:13 -05'00' 6 00;37:19 Tech Review / Date Admin Review of Gate

Florida Department of Law Enforcement **Alcohol Testing Program**

DEPARTMENT INSPECTION REPORT - INTOXILYZER 8000

Agency: FDLE

Time of Inspection: 15:15

Date of Inspection: 12/14/2020

Serial Number: 80-000219

Software: 8100.27

Check or Test	YES	ИО	Check or Test	YES	NO
Diagnostic Check			Date and/or Time Adjusted		
(Pre-Inspection): OK	Yes				No
Minimum Sample Volume			Barometric Pressure Sensor		
Check: OK	Yes		Check: OK	Yes	
Alcohol Free Subject			Mouth Alcohol Test:		
Test: 0.000	Yes		Slope Not Met	Yes	
Interferent Detect Test:			Diagnostic Check		
Interferent Detect	Yes		(Post-Inspection): OK	Yes	

Alcohol Free Test (g/210L)	0.05g/210L Test (g/210L) Lot#:201905A Exp: 05/14/2021	0.08g/210L Test (g/210L) Lot#:202010B Exp: 10/05/2022	0.20g/210L Test (g/210L) Lot#:201904D Exp: 04/30/2021	0.08 g/210L Dry Gas Std Test (g/210L) Lot#:AG011102 Exp: 04/20/2022
0.000	0.048	0.079	0.200	0.078
0.000	0.048	0.079	0.200	0.078
0.000	0.048	0.079	0.200	0.078
0.000	0.049	0.079	0.200	0.078
0.000	0.048	0.079	0.200	0.078
0.000	0.049	0.080	0.200	0.078
0.000	0.048	0.079	0.200	0.078
0.000	0.048	0.079	0.200	0.078
0.000	0.048	0.079	0.200	0.078
0.000	0.049	0.080	0.200	0.078
Standard Deviations	0.0004	0.0004	0.0000	0.0000

Average Standard Deviation of 0.05, 0.08 and 0.20 g/210L Tests: 0.0002 Number of Simulators Used: 5 Remarks:

) with Chapter 11D-8, FAC. The above instrument complies (X) does not comply (

I certify that I performed this inspection in accordance with the provisions of Chapter 11D-8, FAC.

ISRAEL Signature and Printed Name

12/14/2020

2020.1 -05'00'

Date

Stability Checks

FDL6 //red_gas_= - Musel_8100 12/19/2826 Software: 6100		86-300236	intokilyzen - A Model 6600 12/11/2521 Software: 8186.1	SN	60-000209	FOLS Indoxilyzer in M Model 8000 12/11/2020 Software: 8100	SK 88%
Test	g/218L	7;me	Test	g/219L	Tine	Test	g/2101
Air Blank Control Test St Average Sto Dev Rel Sto Dev(%)	0.049 0.000 ats 0.0490 0.0900	:5: 21 !5: 21 !5: 22 !5: 23 !5: 23 !5: 24 !5: 24	Air Blank Control Test Sta	2,079 0,000 955 9,0790 0,0000	15:26 35:27 15:27 15:28 15:28 15:29 15:30	Air Blank Control Test Air Blank Control Test Air Blank Control Test Air Blank Control Test SI Average Std Dav Rel Std DevC&	0,2000 0,0000

wet

Operatoris Signature

1/2	1
Operator s	Signature

Tine

15:31 15:31 15:32 15:33 (5:33 ,5:34 15:34

FOLE Intomblyzer Aud Madel 8000 12/11/2820 Software: 8100.07	\$r	90-000219
Test	g/213L	Tin:
Control Test Air Blank Control Test Air Blank Control Test Air Blank Control Test Stat Average	0.000 0.079 0.000 0.079 0.000 5 2.0790 0.0000	(5) 36 (5) 36 (5) 37 (5) 38 (5) 38 (5) 38

Operator's Signature

2020.12 .16 00:36:4 0 -05'00'



Calibration Certificate

Florida Department of Law Enforcement Alcohol Testing Program 2729 Fort Knox Blvd. Tallahassee, FL 32308 Bldg. 2, Suite 1300

FDLE/ATP Form 36 - Department Inspection Procedures - Intoxilyzer 8000. This is to certify the calibration of Intoxilyzer 8000 serial number 80-000219, manufactured by CMI, Inc. was calibrated in accordance with

All recults are reported in a/210 I		Calibration Time:	Calibration Date:	Owning Agency:	Serial Number:
		<u>15:15</u>	12/14/2020	FDLE	80-000219
	0.080 g/ 210 L Dry Gas Control	$0.200 \mathrm{g}/210 \mathrm{L}$	0.080 g/210 L	$0.050 \mathrm{g}/210 \mathrm{L}$	UNCERTAINTY* ±
	0.005	0.007	0.005	0.004	

All results are reported in g/ 210 L.

*Uncertainty is based on fleet-wide data and is expressed to a 99.73% level of confidence (k=3). Bias is limited by calibration acceptance criteria. All calibration results must be within ± 0.005 or 5%, whichever is greater, of the target alcohol concentration.

The instrument results before and after any adjustment are found in the associated pre and post stability checks

TRACEABILITY INFORMATION

with ISO 17034 and ISO/ IEC 17025 Standards. This instrument was calibrated using solutions prepared by Alcohol Countermeasure Systems, Inc. (ACS). ACS prepared and certified these CRMs in accordance

Precision Metrology in accordance with ISO/ IEC 17025 standards. Simulator temperatures are traceable to NIST. Thermometer temperatures are checked with NIST traceable Eutechnics 4400 digital thermometers calibrated by

controls prepared and certified the CRMs in accordance with ISO Guide 34 and ISO/ IEC 17025 standards. Dry gas control measurements are traceable to NIST through the uses of CRMs supplied by an accredited CRM supplier. The supplier of dry gas standard

without written approval of the Florida Department of This document shall not be reproduced except in full, Law Enforcement Alcohol Testing Program

12/14/2020

Department Inspector SOTO

Page 1 of 1





Issuing Authority: Alcohol Testing Program FDLE/ATP Form 69 April 2020

Service · Integrity · Respect · Quality