



INSTRUMENT PROCESSING SHEET

Agency Madison County

S/N 80-000779

Florida Department of Law Enforcement

Date In 3/12/2020

DI Completion Date 3/16/20

Ship  P/U  H/D  CMI  EE

| <b>Intake</b> Performed By <u>DP</u><br><input checked="" type="checkbox"/> Annual<br><input type="checkbox"/> Registration<br><input type="checkbox"/> Return from CMI / EE<br>Visual Inspection:<br><input checked="" type="checkbox"/> Case <input checked="" type="checkbox"/> Handle<br><input checked="" type="checkbox"/> Keyboard <input checked="" type="checkbox"/> Dry Gas Shelf<br><input checked="" type="checkbox"/> Feet <input checked="" type="checkbox"/> Breath Tube<br><input checked="" type="checkbox"/> Ports <input checked="" type="checkbox"/> Screws Tight<br>Other Equipment/ Accessories:<br><input type="checkbox"/> Power cord <input type="checkbox"/> Printer Cable<br><input type="checkbox"/> Static Bag <input type="checkbox"/> 12V DC Cable<br>Notes: _____<br>_____<br>_____ |               | <b>Quality Checks</b> Performed By <u>DP</u><br><input checked="" type="checkbox"/> Breath Tube Screen<br><input checked="" type="checkbox"/> Replace External O-Rings<br><input checked="" type="checkbox"/> Instrument Set Up Verified<br><input checked="" type="checkbox"/> R-Value <u>222</u><br><input checked="" type="checkbox"/> Flow Verification (L/s)<br>Flow Column # <u>ATP-102</u><br>32 mm <u>0.152</u> (.139 - .169)<br>36 mm <u>0.167</u> (.156 - .190)<br>53 mm <u>0.238</u> (.228 - .278)<br>103 mm <u>0.511</u> (.447 - .547)<br><input checked="" type="checkbox"/> Barometric Pressure Check<br>Gauge ID # <u>26932</u><br><input checked="" type="checkbox"/> Stability Checks |               | <b>Flow Calibration</b> Performed By _____<br>Flow Column # _____<br><input type="checkbox"/> 5L/min - 17mm<br><input type="checkbox"/> 15L/min - 53mm<br><input type="checkbox"/> 30L/min - 103mm<br><input type="checkbox"/> R-Value _____<br><input type="checkbox"/> Post Calibration Verification (L/s)<br>Flow Column # _____<br>32 mm _____ (.139 - .169)<br>36 mm _____ (.156 - .190)<br>53 mm _____ (.228 - .278)<br>103 mm _____ (.447 - .547) |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
|---|---------------|--|---------------|--|------------|-----------|-------|---------------|-------------------------------------|-------|---------------|-------------------------------------|-------|---------------|-------------------------------------|-----------|------------|--------------------------------------|---|--|--|-------|--|--|--|-----------|------------|--|--|--|--|-----------|---------------|-------|--------------|-------------|---------------|-------|---------------|-------|---------------|-------|---------------|
| <b>Final Release Date</b><br><p style="text-align: center;"><b>FDLE</b><br/><br/>MAR 16 2020<br/><br/>Alcohol Testing Program</p>   |               | <table border="1"> <thead> <tr> <th>Simulator</th> <th>Serial #</th> <th>Lot #/Exp</th> </tr> </thead> <tbody> <tr> <td>0.050</td> <td><u>SD1021</u></td> <td><u>201905A</u><br/><u>05-14-2021</u></td> </tr> <tr> <td>0.080</td> <td><u>DR1275</u></td> <td><u>201905B</u><br/><u>05-14-2021</u></td> </tr> <tr> <td>0.200</td> <td><u>SD1011</u></td> <td><u>201904D</u><br/><u>04-30-2021</u></td> </tr> <tr> <td>0.080 DGS</td> <td><u>N/A</u></td> <td><u>AG931603</u><br/><u>11-12-2021</u></td> </tr> </tbody> </table>   |               | Simulator  | Serial #   | Lot #/Exp | 0.050 | <u>SD1021</u> | <u>201905A</u><br><u>05-14-2021</u> | 0.080 | <u>DR1275</u> | <u>201905B</u><br><u>05-14-2021</u> | 0.200 | <u>SD1011</u> | <u>201904D</u><br><u>04-30-2021</u> | 0.080 DGS | <u>N/A</u> | <u>AG931603</u><br><u>11-12-2021</u> | <b>Maintenance</b> Performed By _____<br><input type="checkbox"/> Battery Replacement<br><input type="checkbox"/> Dry Gas Regulator Replacement<br><input type="checkbox"/> Breath Tube Replacement<br><input type="checkbox"/> Other _____ |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| Simulator   | Serial #      | Lot #/Exp  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| 0.050   | <u>SD1021</u> | <u>201905A</u><br><u>05-14-2021</u>  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| 0.080   | <u>DR1275</u> | <u>201905B</u><br><u>05-14-2021</u>  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| 0.200   | <u>SD1011</u> | <u>201904D</u><br><u>04-30-2021</u>  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| 0.080 DGS   | <u>N/A</u>    | <u>AG931603</u><br><u>11-12-2021</u>   |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| <b>Calibration Adjustment</b> Performed By _____<br>Barometric Pressure Gauge _____ ID # _____  |               | <b>Department Inspection</b> Performed By <u>SP</u><br>Barometric Pressure ID# <u>28421</u><br>Gauge <u>1024</u> Instrument <u>1021</u><br>Mouth Alcohol Solution Lot # <u>2019-B</u><br>Acetone Stock Solution Lot # <u>2019-A</u>  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| <table border="1"> <thead> <tr> <th>Simulator</th> <th>Serial Number</th> <th>Lot Number</th> <th>Expiration</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td></td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>0.040</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.100</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.200</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.300</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.080 DGS</td> <td><u>N/A</u></td> <td></td> <td></td> </tr> </tbody> </table>  |               | Simulator  | Serial Number | Lot Number   | Expiration | 0.000     |       | N/A           | N/A                                 | 0.040 |               |                                     |       | 0.100         |                                     |           |            | 0.200                                |   |  |  | 0.300 |  |  |  | 0.080 DGS | <u>N/A</u> |  |  | <table border="1"> <thead> <tr> <th>Simulator</th> <th>Serial Number</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td><u>G8144</u></td> </tr> <tr> <td>Interferent</td> <td><u>DR3855</u></td> </tr> <tr> <td>0.050</td> <td><u>SD1021</u></td> </tr> <tr> <td>0.080</td> <td><u>DR1275</u></td> </tr> <tr> <td>0.200</td> <td><u>SD1011</u></td> </tr> </tbody> </table> |  | Simulator | Serial Number | 0.000 | <u>G8144</u> | Interferent | <u>DR3855</u> | 0.050 | <u>SD1021</u> | 0.080 | <u>DR1275</u> | 0.200 | <u>SD1011</u> |
| Simulator   | Serial Number | Lot Number   | Expiration    |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| 0.000   |               | N/A  | N/A           |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| 0.040   |               |  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| 0.100   |               |  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| 0.200   |               |  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| 0.300   |               |  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| 0.080 DGS   | <u>N/A</u>    |  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| Simulator   | Serial Number |  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| 0.000   | <u>G8144</u>  |  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| Interferent   | <u>DR3855</u> |  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| 0.050   | <u>SD1021</u> |  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| 0.080   | <u>DR1275</u> |  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| 0.200   | <u>SD1011</u> |  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| <input type="checkbox"/> Post Calibration Adjustment Stability Checks   |               | <b>Attachments</b><br><input checked="" type="checkbox"/> Form 41 <input type="checkbox"/> Post-Stability Checks<br><input checked="" type="checkbox"/> Stability Checks <input type="checkbox"/> Flow Calibration<br><input checked="" type="checkbox"/> Calibration Certificate <input type="checkbox"/> Form 40<br><input type="checkbox"/> Calibration Adjustment <input type="checkbox"/> Other _____   |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
| Notes/Suggested Service: _____<br>_____<br>_____<br>_____<br>_____  |               | <input checked="" type="checkbox"/> Instrument Complies with Chapter 11D-8, FAC<br><input type="checkbox"/> Instrument Does Not Comply with Chapter 11D-8, FAC<br><input checked="" type="checkbox"/> Return to/Place into Evidentiary Use<br><input type="checkbox"/> Remain Out of Evidentiary Use<br><input checked="" type="checkbox"/> Conduct an Agency Inspection Before Evidentiary Use  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |
|   |               | <u>DP</u> 3/16/20 <u>Brett Kiehlund</u> 3/16/2020<br>Tech Review / Date Admin Review / Date  |               |  |            |           |       |               |                                     |       |               |                                     |       |               |                                     |           |            |                                      |   |  |  |       |  |  |  |           |            |  |  |  |  |           |               |       |              |             |               |       |               |       |               |       |               |



# Calibration Certificate

Florida Department of Law Enforcement  
Alcohol Testing Program  
2729 Fort Knox Blvd.  
Bldg. 2, Suite 1300  
Tallahassee, FL 32308

This is to certify the calibration of Intoxilyzer 8000 serial number 80-000779, manufactured by CMI, Inc. was calibrated in accordance with FDLE/ATP Form 36 - Department Inspection Procedures - Intoxilyzer 8000.

|                   |                          |                                |       |
|-------------------|--------------------------|--------------------------------|-------|
| Serial Number:    | <u>80-000779</u>         | UNCERTAINTY* ±                 |       |
| Owning Agency:    | <u>MADISON COUNTY SO</u> | 0.050 g/ 210 L                 | 0.004 |
| Calibration Date: | <u>03/16/2020</u>        | 0.080 g/ 210 L                 | 0.005 |
| Calibration Time: | <u>12:37</u>             | 0.200 g/ 210 L                 | 0.007 |
|                   |                          | 0.080 g/ 210 L Dry Gas Control | 0.005 |

All results are reported in g/ 210 L.

Bias is limited by calibration acceptance criteria. All calibration results must be within ± 0.005 or 5%, whichever is greater, of the target alcohol concentration.  
\*Uncertainty is based on fleet-wide data and is expressed to a 99.73% level of confidence (k=3).

### TRACEABILITY INFORMATION

This instrument was calibrated using solutions prepared by Alcohol Countermeasure Systems, Inc. (ACS). ACS prepared and certified these CRMs in accordance with ISO 17034 and ISO/ IEC 17025 Standards.

Simulator temperatures are traceable to NIST. Thermometer temperatures are checked with NIST traceable Eutechnics 4400 digital thermometers calibrated by Precision Metrology in accordance with ISO/ IEC 17025 standards.

Dry gas control measurements are traceable to NIST through the uses of CRMs supplied by an accredited CRM supplier. The supplier of dry gas standard controls prepared and certified the CRMs in accordance with ISO Guide 34 and ISO/ IEC 17025 standards.

This document shall not be reproduced except in full, without written approval of the Florida Department of Law Enforcement Alcohol Testing Program.

*Shayla Platt*

03/16/2020

Date

SHAYLA D PLATT,

Department Inspector

FDLE/ATP Form 69 January 2020  
Issuing Authority: Alcohol Testing Program

Service • Integrity • Respect • Quality

*QPM 15K 3/16/2020*

# Florida Department of Law Enforcement Alcohol Testing Program

## DEPARTMENT INSPECTION REPORT - INTOXILYZER 8000

Agency: MADISON COUNTY SO  
Time of Inspection: 12:37

Date of Inspection: 03/16/2020

Serial Number: 80-000779  
Software: 8100.27

| Check or Test                               | YES | NO | Check or Test                          | YES | NO |
|---|-----|----|--|-----|----|
| Diagnostic Check (Pre-Inspection): OK       | Yes |    | Date and/or Time Adjusted              |     | No |
| Minimum Sample Volume Check: OK             | Yes |    | Barometric Pressure Sensor Check: OK   | Yes |    |
| Alcohol Free Subject Test: 0.000            | Yes |    | Mouth Alcohol Test: Slope Not Met      | Yes |    |
| Interferent Detect Test: Interferent Detect | Yes |    | Diagnostic Check (Post-Inspection): OK | Yes |    |

| Alcohol Free Test (g/210L) | 0.05g/210L Test (g/210L)<br>Lot#:201905A<br>Exp: 05/14/2021 | 0.08g/210L Test (g/210L)<br>Lot#:201905B<br>Exp: 05/14/2021 | 0.20g/210L Test (g/210L)<br>Lot#:201904D<br>Exp: 04/30/2021 | 0.08 g/210L Dry Gas Std Test (g/210L)<br>Lot#:AG931603<br>Exp: 11/12/2021 |
|----------------------------|---|---|---|---|
| 0.000                      | 0.048   | 0.080   | 0.200   | 0.081   |
| 0.000                      | 0.047   | 0.080   | 0.202   | 0.080   |
| 0.000                      | 0.049   | 0.080   | 0.202   | 0.080   |
| 0.000                      | 0.048   | 0.080   | 0.202   | 0.080   |
| 0.000                      | 0.049   | 0.080   | 0.201   | 0.080   |
| 0.000                      | 0.048   | 0.080   | 0.203   | 0.080   |
| 0.000                      | 0.049   | 0.080   | 0.204   | 0.080   |
| 0.000                      | 0.049   | 0.080   | 0.205   | 0.081   |
| 0.000                      | 0.049   | 0.080   | 0.204   | 0.081   |
| 0.000                      | 0.050   | 0.080   | 0.205   | 0.081   |

|                     |        |        |        |        |
|---------------------|--------|--------|--------|--------|
| Standard Deviations | 0.0008 | 0.0000 | 0.0016 | 0.0005 |
|---------------------|--------|--------|--------|--------|

Average Standard Deviation of 0.05, 0.08 and 0.20 g/210L Tests: 0.0007 Number of Simulators Used: 5

Remarks:

PPM  
13K  
3/16/2020

The above instrument complies (  ) does not comply (  ) with Chapter 11D-8, FAC.

I certify that I performed this inspection in accordance with the provisions of Chapter 11D-8, FAC.

Shayla Platt

SHAYLA D PLATT

Signature and Printed Name

03/16/2020  
Date

# Stability Checks

MADISON COUNTY SO  
 Intoxilyzer - Alcohol Analyzer  
 Model 8000 SN 80-000779  
 03/13/2020  
 Software: 8100.27

| Test               | g/210L | Time  |
|--------------------|--------|-------|
| Air Blank          | 0.000  | 14:45 |
| Control Test       | 0.049  | 14:46 |
| Air Blank          | 0.000  | 14:47 |
| Control Test       | 0.048  | 14:47 |
| Air Blank          | 0.000  | 14:48 |
| Control Test       | 0.050  | 14:49 |
| Air Blank          | 0.000  | 14:49 |
| Control Test Stats |        |       |
| Average            | 0.0490 |       |
| Std Dev            | 0.0010 |       |
| Rel Std Dev(%)     | 2.0408 |       |

*SS*  
 Operator's Signature

MADISON COUNTY SO  
 Intoxilyzer - Alcohol Analyzer  
 Model 8000 SN 80-000779  
 03/13/2020  
 Software: 8100.27

| Test               | g/210L | Time  |
|--------------------|--------|-------|
| Air Blank          | 0.000  | 14:50 |
| Control Test       | 0.080  | 14:51 |
| Air Blank          | 0.000  | 14:51 |
| Control Test       | 0.080  | 14:52 |
| Air Blank          | 0.000  | 14:53 |
| Control Test       | 0.080  | 14:53 |
| Air Blank          | 0.000  | 14:54 |
| Control Test Stats |        |       |
| Average            | 0.0800 |       |
| Std Dev            | 0.0000 |       |
| Rel Std Dev(%)     | 0.0000 |       |

wet

*SS*  
 Operator's Signature

MADISON COUNTY SO  
 Intoxilyzer - Alcohol Analyzer  
 Model 8000 SN 80-000779  
 03/13/2020  
 Software: 8100.27

| Test               | g/210L | Time  |
|--------------------|--------|-------|
| Air Blank          | 0.000  | 14:58 |
| Control Test       | 0.202  | 14:58 |
| Air Blank          | 0.000  | 14:59 |
| Control Test       | 0.204  | 15:00 |
| Air Blank          | 0.000  | 15:00 |
| Control Test       | 0.204  | 15:01 |
| Air Blank          | 0.000  | 15:01 |
| Control Test Stats |        |       |
| Average            | 0.2033 |       |
| Std Dev            | 0.0012 |       |
| Rel Std Dev(%)     | 0.5579 |       |

*SS*  
 Operator's Signature

MADISON COUNTY SO  
 Intoxilyzer - Alcohol Analyzer  
 Model 8000 SN 80-000779  
 03/13/2020  
 Software: 8100.27

| Test               | g/210L | Time  |
|--------------------|--------|-------|
| Air Blank          | 0.000  | 15:03 |
| Control Test       | 0.078  | 15:03 |
| Air Blank          | 0.000  | 15:04 |
| Control Test       | 0.078  | 15:04 |
| Air Blank          | 0.000  | 15:05 |
| Control Test       | 0.077  | 15:05 |
| Air Blank          | 0.000  | 15:05 |
| Control Test Stats |        |       |
| Average            | 0.0777 |       |
| Std Dev            | 0.0006 |       |
| Rel Std Dev(%)     | 0.7434 |       |

Dry

*SS*  
 Operator's Signature

*pgm*  
*BSK*  
*3/16/2020*