



Agency Blountstown Police Department

S/N 80-000862

Date In 01-16-2023 DI Completion Date 01-17-2023

☐ Ship ☒ P/U ☐ H/D ☐ CMI ☐ EE

Intake	By <u>IS</u>	Quality Checks	By <u>IS</u>	Date <u>01-17-2023</u>	Flow Calibration	By _____	Date _____																																	
☒ Annual ☐ Registration ☐ Return from CMI / EE Visual Inspection: ☒ Case ☒ Handle ☒ Keyboard ☒ Dry Gas Shelf ☒ Feet ☒ Breath Tube ☒ Ports ☒ Screws Tight Other Equipment/ Accessories: ☐ Power cord ☐ Printer Cable ☐ Static Bag ☐ 12V DC Cable Notes: Instrument picked up from Agency Inspector by FDLE ATP member. 		☒ Breath Tube Screen ☒ Replace External O-Rings ☒ Instrument Set Up Verified ☒ R-Value <u>173</u> ☒ Flow Verification (L/s) Flow Column # <u>ATP-105</u> 32 mm <u>0.156</u> (.139 - .169) 36 mm <u>0.167</u> (.156 - .190) 53 mm <u>0.242</u> (.228 - .278) 103 mm <u>0.527</u> (.447 - .547) ☒ Barometric Pressure Check Gauge ID # <u>30793</u> ☒ Stability Checks <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 5px;"> <thead> <tr style="background-color: #cccccc;"> <th style="padding: 5px;">Simulator</th> <th style="padding: 5px;">Serial #</th> <th style="padding: 5px;">Lot #/Exp</th> </tr> </thead> <tbody> <tr> <td style="padding: 5px;">0.050</td> <td style="padding: 5px;">MP6291</td> <td style="padding: 5px;">202201C 01-11-2024</td> </tr> <tr> <td style="padding: 5px;">0.080</td> <td style="padding: 5px;">MP6292</td> <td style="padding: 5px;">202201D 01-18-2024</td> </tr> <tr> <td style="padding: 5px;">0.200</td> <td style="padding: 5px;">MP6293</td> <td style="padding: 5px;">202201E 01-18-2024</td> </tr> <tr> <td style="padding: 5px;">0.080 DGS</td> <td style="padding: 5px;">N/A</td> <td style="padding: 5px;">AG113403 05-14-2023</td> </tr> </tbody> </table>	Simulator	Serial #	Lot #/Exp	0.050	MP6291	202201C 01-11-2024	0.080	MP6292	202201D 01-18-2024	0.200	MP6293	202201E 01-18-2024	0.080 DGS	N/A	AG113403 05-14-2023			Flow Column # _____ ☐ 5L/min – 17mm ☐ 15L/min – 53mm ☐ 30L/min – 103mm ☐ R-Value _____ ☐ Post Calibration Verification (L/s) Flow Column # _____ 32 mm _____ (.139 - .169) 36 mm _____ (.156 - .190) 53 mm _____ (.228 - .278) 103 mm _____ (.447 - .547)																				
Simulator	Serial #	Lot #/Exp																																						
0.050	MP6291	202201C 01-11-2024																																						
0.080	MP6292	202201D 01-18-2024																																						
0.200	MP6293	202201E 01-18-2024																																						
0.080 DGS	N/A	AG113403 05-14-2023																																						
Calibration Adjustment				By _____	Department Inspection			By <u>IS</u>																																
Barometric Pressure Gauge _____ ID # _____				Barometric Pressure ID# <u>30793</u>																																				
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr style="background-color: #cccccc;"> <th style="padding: 5px;">Simulator</th> <th style="padding: 5px;">Serial #</th> <th style="padding: 5px;">Lot #</th> <th style="padding: 5px;">Expiration</th> </tr> </thead> <tbody> <tr><td style="padding: 5px;">0.000</td><td style="padding: 5px;"></td><td style="padding: 5px;">N/A</td><td style="padding: 5px;">N/A</td></tr> <tr><td style="padding: 5px;">0.040</td><td style="padding: 5px;"></td><td style="padding: 5px;"></td><td style="padding: 5px;"></td></tr> <tr><td style="padding: 5px;">0.100</td><td style="padding: 5px;"></td><td style="padding: 5px;"></td><td style="padding: 5px;"></td></tr> <tr><td style="padding: 5px;">0.200</td><td style="padding: 5px;"></td><td style="padding: 5px;"></td><td style="padding: 5px;"></td></tr> <tr><td style="padding: 5px;">0.300</td><td style="padding: 5px;"></td><td style="padding: 5px;"></td><td style="padding: 5px;"></td></tr> <tr><td style="padding: 5px;">0.080 DGS</td><td style="padding: 5px;">N/A</td><td style="padding: 5px;"></td><td style="padding: 5px;"></td></tr> </tbody> </table>				Simulator	Serial #	Lot #	Expiration	0.000		N/A	N/A	0.040				0.100				0.200				0.300				0.080 DGS	N/A			Gauge <u>1012</u> Instrument <u>1010</u>								
Simulator	Serial #	Lot #	Expiration																																					
0.000		N/A	N/A																																					
0.040																																								
0.100																																								
0.200																																								
0.300																																								
0.080 DGS	N/A																																							
				Mouth Alcohol Solution Lot # <u>2022-A</u>																																				
				Acetone Stock Solution Lot # <u>2022-B</u>																																				
☐ Post Calibration Adjustment Stability Checks <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr style="background-color: #cccccc;"> <th style="padding: 5px;">Simulator</th> <th style="padding: 5px;">Serial #</th> <th style="padding: 5px;">Lot #</th> <th style="padding: 5px;">Expiration</th> </tr> </thead> <tbody> <tr><td style="padding: 5px;">0.050</td><td style="padding: 5px;"></td><td style="padding: 5px;"></td><td style="padding: 5px;"></td></tr> <tr><td style="padding: 5px;">0.080</td><td style="padding: 5px;"></td><td style="padding: 5px;"></td><td style="padding: 5px;"></td></tr> <tr><td style="padding: 5px;">0.200</td><td style="padding: 5px;"></td><td style="padding: 5px;"></td><td style="padding: 5px;"></td></tr> <tr><td style="padding: 5px;">0.080 DGS</td><td style="padding: 5px;">N/A</td><td style="padding: 5px;"></td><td style="padding: 5px;"></td></tr> </tbody> </table>				Simulator	Serial #	Lot #	Expiration	0.050				0.080				0.200				0.080 DGS	N/A			<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr style="background-color: #cccccc;"> <th style="padding: 5px;">Simulator</th> <th style="padding: 5px;">Serial Number</th> </tr> </thead> <tbody> <tr><td style="padding: 5px;">0.000</td><td style="padding: 5px;">MP6289</td></tr> <tr><td style="padding: 5px;">Interferent</td><td style="padding: 5px;">MP6290</td></tr> <tr><td style="padding: 5px;">0.050</td><td style="padding: 5px;">MP6291</td></tr> <tr><td style="padding: 5px;">0.080</td><td style="padding: 5px;">MP6292</td></tr> <tr><td style="padding: 5px;">0.200</td><td style="padding: 5px;">MP6293</td></tr> </tbody> </table>					Simulator	Serial Number	0.000	MP6289	Interferent	MP6290	0.050	MP6291	0.080	MP6292	0.200	MP6293
Simulator	Serial #	Lot #	Expiration																																					
0.050																																								
0.080																																								
0.200																																								
0.080 DGS	N/A																																							
Simulator	Serial Number																																							
0.000	MP6289																																							
Interferent	MP6290																																							
0.050	MP6291																																							
0.080	MP6292																																							
0.200	MP6293																																							
Attachments																																								
☒ Form 41 ☒ Stability Checks ☒ Calibration Certificate ☐ Calibration Adjustment				☐ Post-Stability Checks ☐ Flow Calibration ☐ Form 40 ☐ Other _____																																				
☒ Instrument Complies with Chapter 11D-8, FAC ☐ Instrument Does Not Comply with Chapter 11D-8, FAC ☒ Return to/Place into Evidentiary Use ☐ Remain Out of Evidentiary Use ☒ Conduct an Agency Inspection Before Evidentiary Use																																								
Notes/Suggested Service: _____ _____ _____ _____ _____ _____ _____				David Eliezer Reyes-Rivera Digitally signed by David Eliezer Reyes-Rivera Date: 2023.01.17 12:29:08 -05'00' Phil Nicodemo Digitally signed by Phil Nicodemmo Date: 2023.01.17 14:34:38 -05'00' Tech Review / Date _____ Admin Review / Date _____																																				

Florida Department of Law Enforcement Alcohol Testing Program

DEPARTMENT INSPECTION REPORT - INTOXILYZER 8000

Agency: BLOUNTSTOWN PD
Time of Inspection: 09:30

Date of Inspection: 01/17/2023

Serial Number: 80-000862
Software: 8100.27

Check or Test	YES	NO	Check or Test	YES	NO
Diagnostic Check (Pre-Inspection): OK	Yes		Date and/or Time Adjusted		No
Minimum Sample Volume Check: OK	Yes		Barometric Pressure Sensor Check: OK	Yes	
Alcohol Free Subject Test: 0.000	Yes		Mouth Alcohol Test: Slope Not Met	Yes	
Interferent Detect Test: Interferent Detect	Yes		Diagnostic Check (Post-Inspection): OK	Yes	

Alcohol Free Test (g/210L)	0.05g/210L Test (g/210L) Lot#:202201C Exp: 01/11/2024	0.08g/210L Test (g/210L) Lot#:202201D Exp: 01/18/2024	0.20g/210L Test (g/210L) Lot#:202201E Exp: 01/18/2024	0.08 g/210L Dry Gas Std Test (g/210L) Lot#:AG113403 Exp: 05/14/2023
0.000	0.049	0.079	0.205	0.080
0.000	0.049	0.079	0.204	0.080
0.000	0.049	0.078	0.204	0.080
0.000	0.049	0.079	0.204	0.080
0.000	0.050	0.079	0.204	0.080
0.000	0.049	0.079	0.204	0.080
0.000	0.050	0.079	0.205	0.080
0.000	0.049	0.079	0.204	0.080
0.000	0.049	0.079	0.204	0.080
0.000	0.049	0.079	0.204	0.080

Standard Deviations	0.0004	0.0003	0.0004	0.0000
---------------------	--------	--------	--------	--------

Average Standard Deviation of 0.05, 0.08 and 0.20 g/210L Tests: 0.0002 Number of Simulators Used: 5

Remarks:

The above instrument complies (☒) does not comply (☐) with Chapter 11D-8, FAC.

I certify that I performed this inspection in accordance with the provisions of Chapter 11D-8, FAC.

Israel Soto

ISRAEL SOTO

Signature and Printed Name

01/17/2023
Date

Stability Checks

BLOUNTSTOWN PD
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-000862
01/17/2023
Software: 8100.27

Test	g/210L	Time
Air Blank	0.000	07:38
Control Test	0.049	07:38
Air Blank	0.000	07:39
Control Test	0.048	07:40
Air Blank	0.000	07:40
Control Test	0.049	07:41
Air Blank	0.000	07:41
Control Test Stats		
Average	0.0487	
Std Dev	0.0006	
Rel Std Dev(%)	1.1863	

Operator's Signature

BLOUNTSTOWN PD
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-000862
01/17/2023
Software: 8100.27

Test	g/210L	Time
Air Blank	0.000	07:42
Control Test	0.080	07:43
Air Blank	0.000	07:44
Control Test	0.079	07:44
Air Blank	0.000	07:45
Control Test	0.078	07:46
Air Blank	0.000	07:46
Control Test Stats		
Average	0.0790	
Std Dev	0.0010	
Rel Std Dev(%)	1.2658	

wet

Operator's Signature

BLOUNTSTOWN PD
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-000862
01/17/2023
Software: 8100.27

Test	g/210L	Time
Air Blank	0.000	07:47
Control Test	0.204	07:48
Air Blank	0.000	07:48
Control Test	0.202	07:49
Air Blank	0.000	07:50
Control Test	0.201	07:50
Air Blank	0.000	07:51
Control Test Stats		
Average	0.2023	
Std Dev	0.0015	
Rel Std Dev(%)	0.7550	

Operator's Signature

BLOUNTSTOWN PD
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-000862
01/17/2023
Software: 8100.27

Test	g/210L	Time
Air Blank	0.000	07:53
Control Test	0.081	07:54
Air Blank	0.000	07:54
Control Test	0.081	07:55
Air Blank	0.000	07:55
Control Test	0.081	07:55
Air Blank	0.000	07:56
Control Test Stats		
Average	0.0810	
Std Dev	0.0000	
Rel Std Dev(%)	0.0000	

Dry

Operator's Signature



Calibration Certificate

Florida Department of Law Enforcement
Alcohol Testing Program
2331 Phillips Road.
Suite B1032
Tallahassee, FL 32308

This is to certify the calibration of Intoxilyzer 8000 serial number 80-000862, manufactured by CMI, Inc. was calibrated in accordance with FDLE/ATP Form 36 - Department Inspection Procedures - Intoxilyzer 8000.

Serial Number:	<u>80-000862</u>	UNCERTAINTY* $\pm$	
Owning Agency:	<u>BLOUNTSTOWN PD</u>	0.050 g/ 210 L	0.004
Calibration Date:	<u>01/17/2023</u>	0.080 g/ 210 L	0.004
Calibration Time:	<u>09:30</u>	0.200 g/ 210 L	0.007
		0.080 g/ 210 L Dry Gas Control	0.005

All results are reported in g/210 L.

Bias is limited by calibration acceptance criteria. All calibration results must be within ± 0.005 or 5%, whichever is greater, of the target alcohol concentration.

*Uncertainty is based on fleet-wide data and is expressed to a 99.73% level of confidence ($k=3$).

The instrument results before and after any adjustment are found in the associated pre and post stability checks.

TRACEABILITY INFORMATION

This instrument was calibrated using solutions prepared by Alcohol Countermeasure Systems, Inc. (ACS). ACS prepared and certified these CRMs in accordance with ISO 17034 and ISO/ IEC 17025 Standards.

Simulator temperatures are traceable to NIST. Simulator temperatures are checked with NIST traceable digital thermometers calibrated by Precision Metrology in accordance with ISO/ IEC 17025 standards.

Dry gas control measurements are traceable to NIST through the use of CRMs supplied by an accredited CRM supplier. The supplier of dry gas standard controls prepared and certified the CRMs in accordance with ISO Guide 34 and ISO/ IEC 17025 standards.

This document shall not be reproduced except in full, without written approval of the Florida Department of Law Enforcement Alcohol Testing Program.

Israel Soto
Soto
Digitally signed by Israel
Date: 2023.01.17 11:53:00
-05'00'

01/17/2023

Date

ISRAEL SOTO,
Department Inspector

FDLE/ATP Form 69 March 2022
Issuing Authority: Alcohol Testing Program

Service • Integrity • Respect • Quality