



INSTRUMENT PROCESSING SHEET

Agency Hendry CSOS/N 80-006234Florida Department of
Law EnforcementDate In 10/12/2023 DI Completion Date 10/13/2023☐ Ship ☒ P/U ☐ H/D ☐ CMI ☐ EE

| Intake | By TDG | Quality Checks | By TDG | Date <u>10/13/2023</u> | Flow Calibration | By | Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---------------|---|------------|---|--|----------|------------|-----------|---------------|-----------------------|--------|-------------|-----------------------|-------|--------|-----------------------|-----------|-------|------------------------|--|-----|--|--|--|--|--|--|-----------|-----|--|--|--|--|--|--|
| <input checked="" type="checkbox"/> Annual <input type="checkbox"/> Registration <input type="checkbox"/> Return from CMI / EE Visual Inspection: <input checked="" type="checkbox"/> Case <input checked="" type="checkbox"/> Handle <input checked="" type="checkbox"/> Keyboard <input checked="" type="checkbox"/> Dry Gas Shelf <input checked="" type="checkbox"/> Feet <input checked="" type="checkbox"/> Breath Tube <input checked="" type="checkbox"/> Ports <input checked="" type="checkbox"/> Screws Tight Other Equipment/ Accessories: <input type="checkbox"/> Power cord <input type="checkbox"/> Printer Cable <input type="checkbox"/> Static Bag <input type="checkbox"/> 12V DC Cable Notes: _____ _____ _____ _____ _____ _____ _____ _____ _____ _____ | | <input checked="" type="checkbox"/> Breath Tube Screen <input checked="" type="checkbox"/> Replace External O-Rings <input checked="" type="checkbox"/> Instrument Set Up Verified <input checked="" type="checkbox"/> R-Value <u>189</u> <input checked="" type="checkbox"/> Flow Verification (L/s) Flow Column # <u>ATP104</u> 32 mm <u>0.152</u> (.139 - .169) 36 mm <u>0.167</u> (.156 - .190) 53 mm <u>0.238</u> (.228 - .278) 103 mm <u>0.507</u> (.447 - .547) <input checked="" type="checkbox"/> Barometric Pressure Check Gauge ID # <u>26932</u> <input checked="" type="checkbox"/> Stability Checks | | | Flow Column # _____ <input type="checkbox"/> 5L/min – 17mm <input type="checkbox"/> 15L/min – 53mm <input type="checkbox"/> 30L/min – 103mm <input type="checkbox"/> R-Value _____ <input type="checkbox"/> Post Calibration Verification (L/s) Flow Column # _____ 32 mm _____ (.139 - .169) 36 mm _____ (.156 - .190) 53 mm _____ (.228 - .278) 103 mm _____ (.447 - .547) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | <table border="1"><thead><tr><th>Simulator</th><th>Serial #</th><th>Lot #/Exp</th></tr></thead><tbody><tr><td>0.050</td><td>MP5094</td><td>202201C 01/11/2024</td></tr><tr><td>0.080</td><td>MP5095</td><td>202201D 01/18/2024</td></tr><tr><td>0.200</td><td>MP5096</td><td>202201E 01/18/2024</td></tr><tr><td>0.080 DGS</td><td>N/A</td><td>AG223802 08/26/2024</td></tr></tbody></table> | | | Simulator | Serial # | Lot #/Exp | 0.050 | MP5094 | 202201C 01/11/2024 | 0.080 | MP5095 | 202201D 01/18/2024 | 0.200 | MP5096 | 202201E 01/18/2024 | 0.080 DGS | N/A | AG223802 08/26/2024 | Maintenance By _____ <input type="checkbox"/> Battery Replacement <input type="checkbox"/> Dry Gas Regulator Replacement <input type="checkbox"/> Breath Tube Replacement <input type="checkbox"/> Other _____ _____ _____ _____ _____ _____ | | | | | | | | | | | | | | | |
| Simulator | Serial # | Lot #/Exp | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.050 | MP5094 | 202201C 01/11/2024 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 | MP5095 | 202201D 01/18/2024 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.200 | MP5096 | 202201E 01/18/2024 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 DGS | N/A | AG223802 08/26/2024 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Calibration Adjustment By _____ | | | | Department Inspection By TDG _____ | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Barometric Pressure Gauge ID # _____ | | | | Barometric Pressure ID# <u>26932</u> | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"><thead><tr><th>Simulator</th><th>Serial #</th><th>Lot #</th><th>Expiration</th></tr></thead><tbody><tr><td>0.000</td><td></td><td>N/A</td><td>N/A</td></tr><tr><td>0.040</td><td></td><td></td><td></td></tr><tr><td>0.100</td><td></td><td></td><td></td></tr><tr><td>0.200</td><td></td><td></td><td></td></tr><tr><td>0.300</td><td></td><td></td><td></td></tr><tr><td>0.080 DGS</td><td>N/A</td><td></td><td></td></tr></tbody></table> | | | | Simulator | Serial # | Lot # | Expiration | 0.000 | | N/A | N/A | 0.040 | | | | 0.100 | | | | 0.200 | | | | 0.300 | | | | 0.080 DGS | N/A | | | Gauge <u>1010</u> Instrument <u>1011</u> Mouth Alcohol Solution Lot # <u>2023-A</u> Acetone Stock Solution Lot # <u>2022-B</u> | | | |
| Simulator | Serial # | Lot # | Expiration | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.000 | | N/A | N/A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.040 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.100 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.300 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 DGS | N/A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <input type="checkbox"/> Post Calibration Adjustment Stability Checks | | | | <table border="1"><thead><tr><th>Simulator</th><th>Serial Number</th></tr></thead><tbody><tr><td>0.000</td><td>MP4863</td></tr><tr><td>Interferent</td><td>MP5093</td></tr><tr><td>0.050</td><td>MP5094</td></tr><tr><td>0.080</td><td>MP5095</td></tr><tr><td>0.200</td><td>MP5096</td></tr></tbody></table> | | | | Simulator | Serial Number | 0.000 | MP4863 | Interferent | MP5093 | 0.050 | MP5094 | 0.080 | MP5095 | 0.200 | MP5096 | | | | | | | | | | | | | | | | |
| Simulator | Serial Number | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.000 | MP4863 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Interferent | MP5093 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.050 | MP5094 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 | MP5095 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.200 | MP5096 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <table border="1"><thead><tr><th>Simulator</th><th>Serial #</th><th>Lot #</th><th>Expiration</th></tr></thead><tbody><tr><td>0.050</td><td></td><td></td><td></td></tr><tr><td>0.080</td><td></td><td></td><td></td></tr><tr><td>0.200</td><td></td><td></td><td></td></tr><tr><td>0.080 DGS</td><td>N/A</td><td></td><td></td></tr></tbody></table> | | | | Simulator | Serial # | Lot # | Expiration | 0.050 | | | | 0.080 | | | | 0.200 | | | | 0.080 DGS | N/A | | | Attachments <input checked="" type="checkbox"/> Form 41 <input type="checkbox"/> Post-Stability Checks <input checked="" type="checkbox"/> Stability Checks <input type="checkbox"/> Flow Calibration <input checked="" type="checkbox"/> Calibration Certificate <input type="checkbox"/> Form 40 <input type="checkbox"/> Calibration Adjustment <input type="checkbox"/> Other _____ | | | | | | | | | | | |
| Simulator | Serial # | Lot # | Expiration | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.050 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.200 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0.080 DGS | N/A | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Notes/Suggested Service: _____ _____ _____ _____ _____ _____ _____ _____ _____ | | | | <input checked="" type="checkbox"/> Instrument Complies with Chapter 11D-8, FAC <input type="checkbox"/> Instrument Does Not Comply with Chapter 11D-8, FAC <input checked="" type="checkbox"/> Return to/Place into Evidentiary Use <input type="checkbox"/> Remain Out of Evidentiary Use <input checked="" type="checkbox"/> Conduct an Agency Inspection Before Evidentiary Use | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Benjamin Siddoway Digitally signed by Benjamin Siddoway Date: 2023.10.13 15:11:11 -0400 | | | | Phil Nicodemo Digitally signed by Phil Nicodemo Date: 2023.10.13 15:17:35 -0400 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Tech Review / Date | | | | Admin Review / Date | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Stability Checks

| 0.05g/210L | 0.08g/210L | 0.20g/210L | DGS 0.08g/210L |
|--|--|--|--|
| 0.047 to 0.053 | 0.077 to 0.083 | 0.194 to 0.206 | 0.077 to 0.083 |
| ✓ | ✓ | ✓ | ✓ |
| <p>HENDRY COUNTY SO Intoxilyzer - Alcotest Analyzer Model 8000 10/13/2023 Software: 8100.27</p> <p>SN 80-006234</p> <p>Test g/210L Time</p> <p>Air Blank 0.000 10:29</p> <p>Control Test 0.052 10:30</p> <p>Air Blank 0.000 10:30</p> <p>Control Test 0.053 10:31</p> <p>Air Blank 0.000 10:32</p> <p>Control Test 0.053 10:32</p> <p>Air Blank 0.000 10:33</p> <p>Control Test Stats</p> <p>Average 0.0527</p> <p>Std Dev 0.0006</p> <p>Rel Std Dev(%) 1.0962</p> | <p>HENDRY COUNTY SO Intoxilyzer - Alcotest Analyzer Model 8000 10/13/2023 Software: 8100.27</p> <p>SN 80-006234</p> <p>Test g/210L Time</p> <p>Air Blank 0.000 10:37</p> <p>Control Test 0.083 10:38</p> <p>Air Blank 0.000 10:38</p> <p>Control Test 0.082 10:39</p> <p>Air Blank 0.000 10:40</p> <p>Control Test 0.083 10:41</p> <p>Air Blank 0.000 10:41</p> <p>Control Test Stats</p> <p>Average 0.0827</p> <p>Std Dev 0.0006</p> <p>Rel Std Dev(%) 0.6984</p> | <p>HENDRY COUNTY SO Intoxilyzer - Alcotest Analyzer Model 8000 10/13/2023 Software: 8100.27</p> <p>SN 80-006234</p> <p>Test g/210L Time</p> <p>Air Blank 0.000 10:45</p> <p>Control Test 0.206 10:46</p> <p>Air Blank 0.000 10:46</p> <p>Control Test 0.205 10:47</p> <p>Air Blank 0.000 10:48</p> <p>Control Test 0.205 10:49</p> <p>Air Blank 0.000 10:49</p> <p>Control Test Stats</p> <p>Average 0.2053</p> <p>Std Dev 0.0006</p> <p>Rel Std Dev(%) 0.2812</p> | <p>HENDRY COUNTY SO Intoxilyzer - Alcotest Analyzer Model 8000 10/13/2023 Software: 8100.27</p> <p>SN 80-006234</p> <p>Test g/210L Time</p> <p>Air Blank 0.000 10:51</p> <p>Control Test 0.081 10:51</p> <p>Air Blank 0.000 10:51</p> <p>Control Test 0.081 10:52</p> <p>Air Blank 0.000 10:52</p> <p>Control Test 0.081 10:53</p> <p>Air Blank 0.000 10:53</p> <p>Control Test Stats</p> <p>Average 0.0810</p> <p>Std Dev 0.0000</p> <p>Rel Std Dev(%) 0.0000</p> |
| <p>ML</p> <p>Operator's Signature</p> | <p>ML</p> <p>Operator's Signature</p> | <p>ML</p> <p>Operator's Signature</p> | <p>ML</p> <p>Operator's Signature</p> |

Florida Department of Law Enforcement Alcohol Testing Program

DEPARTMENT INSPECTION REPORT - INTOXILYZER 8000

Agency: HENDRY COUNTY SO
Time of Inspection: 14:47

Date of Inspection: 10/13/2023

Serial Number: 80-006234
Software: 8100.27

| Check or Test | YES | NO | Check or Test | YES | NO |
|--|-----|----|---|-----|----|
| Diagnostic Check (Pre-Inspection): OK | Yes | | Date and/or Time Adjusted | | No |
| Minimum Sample Volume Check: OK | Yes | | Barometric Pressure Sensor Check: OK | Yes | |
| Alcohol Free Subject Test: 0.000 | Yes | | Mouth Alcohol Test: Slope Not Met | Yes | |
| Interferent Detect Test: Interferent Detect | Yes | | Diagnostic Check (Post-Inspection): OK | Yes | |

| Alcohol Free Test (g/210L) | 0.05g/210L Test (g/210L) Lot#:202201C Exp: 01/11/2024 | 0.08g/210L Test (g/210L) Lot#:202201D Exp: 01/18/2024 | 0.20g/210L Test (g/210L) Lot#:202201E Exp: 01/18/2024 | 0.08 g/210L Dry Gas Std Test (g/210L) Lot#:AG223802 Exp: 08/26/2024 |
|----------------------------------|--|--|--|---|
| 0.000 | 0.052 | 0.083 | 0.205 | 0.081 |
| 0.000 | 0.052 | 0.083 | 0.205 | 0.081 |
| 0.000 | 0.053 | 0.083 | 0.206 | 0.081 |
| 0.000 | 0.053 | 0.082 | 0.206 | 0.081 |
| 0.000 | 0.052 | 0.082 | 0.206 | 0.081 |
| 0.000 | 0.052 | 0.082 | 0.206 | 0.081 |
| 0.000 | 0.053 | 0.083 | 0.206 | 0.081 |
| 0.000 | 0.052 | 0.083 | 0.206 | 0.081 |
| 0.000 | 0.053 | 0.083 | 0.206 | 0.081 |
| 0.000 | 0.052 | 0.083 | 0.206 | 0.081 |


| | | | | |
|---------------------|--------|--------|--------|--------|
| Standard Deviations | 0.0005 | 0.0004 | 0.0004 | 0.0000 |
|---------------------|--------|--------|--------|--------|

Average Standard Deviation of 0.05, 0.08 and 0.20 g/210L Tests: 0.0003 Number of Simulators Used: 5

Remarks:

The above instrument complies (☒) does not comply (☐) with Chapter 11D-8, FAC.


I certify that I performed this inspection in accordance with the provisions of Chapter 11D-8, FAC.



TAYLOR D GUTSCHOW

Signature and Printed Name

10/13/2023
Date



Calibration Certificate

Florida Department of Law Enforcement
Alcohol Testing Program
4700 Terminal Drive, Suite 1
Ft. Myers, FL 33907

This is to certify the calibration of Intoxilyzer 8000 serial number 80-006234, manufactured by CMI, Inc. was calibrated in accordance with FDLE/ATP Form 36 - Department Inspection Procedures - Intoxilyzer 8000.

| | | | |
|-------------------|-------------------------|--------------------------------|-------|
| Serial Number: | <u>80-006234</u> | UNCERTAINTY* \pm | |
| Owning Agency: | <u>HENDRY COUNTY SO</u> | 0.050 g/ 210 L | 0.004 |
| Calibration Date: | <u>10/13/2023</u> | 0.080 g/ 210 L | 0.004 |
| Calibration Time: | <u>14:47</u> | 0.200 g/ 210 L | 0.007 |
| | | 0.080 g/ 210 L Dry Gas Control | 0.005 |

All results are reported in g/ 210 L.

Bias is limited by calibration acceptance criteria. All calibration results must be within ± 0.005 or 5%, whichever is greater, of the target alcohol concentration.

*Uncertainty is based on fleet-wide data and is expressed to a 99.73% level of confidence ($k=3$).

The instrument results before and after any adjustment are found in the associated pre and post stability checks.

TRACEABILITY INFORMATION

This instrument was calibrated using solutions prepared by Alcohol Countermeasure Systems, Inc. (ACS). ACS prepared and certified these CRMs in accordance with ISO 17034 and ISO/ IEC 17025 Standards.

Simulator temperatures are traceable to NIST. Simulator temperatures are checked with NIST traceable digital thermometers calibrated by Precision Metrology in accordance with ISO/ IEC 17025 standards.

Dry gas control measurements are traceable to NIST through the use of CRMs supplied by an accredited CRM supplier. The supplier of dry gas standard controls prepared and certified the CRMs in accordance with ISO Guide 34 and ISO/ IEC 17025 standards. This document shall not be reproduced except in full, without written approval of the Florida Department of Law Enforcement Alcohol Testing Program.

10/13/2023

Date

Taylor D Gutschow

TAYLOR D GUTSCHOW,

Department Inspector

FDLE/ATP Form 69 December 2021

Issuing Authority: Alcohol Testing Program

Service • Integrity • Respect • Quality