Alcohol Testing Program - Instrument Processing Sheet

Agency: NEW SMYRNA BEACH PD **Instrument Serial Number:** 80-001152

Date In: 1/6/2026 **DI Completion Date:** 1/27/2026 ☑ Ship ☐ P/U ☐ H/D ☐ CMI ☐ EE

Intake By: KTS Date: 1/6/2026

☒ Annual
☐ Dropped Off
☐ Registration
☐ Return from CMI / EE
☐ Training Instrument

Visual Inspection
☒ Case ☒ Handle
☒ Keyboard ☒ Dry Gas Shelf
☒ Feet ☒ Breath Tube
☒ Ports ☒ Screws Tight

Other Equipment/Accessories
☒ Power Cord ☐ Printer Cable
☒ Static Bag ☐ 12V DC Cable

Notes: AI noted instrument testing outside of tolerance for 0.080g/210L. KTS 1/6/26

Quality Checks By: SLH Date: 1/13/2026

☑ Breath Tube Screen
☑ Replace External O-Rings
☑ Instrument Set Up Verified
☑ R-Value: 145 *
☑ Flow Verification (L/s)
Flow Column #: ATP 103 *
32 mm 0.152 (.139-.169)
36 mm 0.167 (.156-.190)
53 mm 0.234 (.228-.278)
103 mm 0.492 (.447-.547)
☑ Barometric Pressure Check
Gauge ID #: 28427
Gauge: 1018 Instrument: 1017
☑ Stability Checks

Simulator	Serial #	Lot#/Exp
0.050	MP5088	202406K 06/19/2026
0.080	MP5089	202406L 06/19/2026
0.200	MP5090	202406N 06/20/2026
0.080 DGS	N/A	AG510701 04/17/2027

Flow Adjustment By:

Flow Column #:
☐ 5L/min – 17mm
☐ 15L/min – 53mm
☐ 30L/min – 103mm
☐ R-Value:
☐ Post Adjustment Verification (L/S)
Flow Column #:
32 mm (.139-.169)
36 mm (.156-.190)
53 mm (.228-.278)
103 mm (.447-.547)

Maintenance By: Date:
☐ Battery Replacement
☐ Dry Gas Regulator Replacement
☐ Tank Sensor Tare
☐ Breath Tube Replacement
☐ Other:

Optical Bench Adjustment By: WKP

Barometric Pressure Gauge: 1028 ID#: 34419

Simulator	Serial #	Lot #	Expiration
0.000	MP6294	N/A	N/A
0.040	MP6295	25090	03/11/2027
0.100	MP6296	25282	08/12/2027
0.200	MP6297	25020	01/14/2027
0.300	MP6298	25150	05/06/27
0.080 DGS	N/A	28424080A3	11/05/2026

☒ Post Optical Bench Adjustment Stability Checks

Simulator	Serial #	Lot #	Expiration
0.050	MP6291	202406K	06/19/2026
0.080	MP6292	202406L	06/19/2026
0.200	MP6293	202406N	06/20/2026
0.080 DGS	N/A	AG510701	04/17/2027

Gauge ID #: 34420
Gauge: 1026 Instrument: 1025

Department Inspection By: SLH

Barometric Pressure ID#: 28662
Gauge: 1024 Instrument: 1025
Mouth Alcohol Solution Lot #: 2025-D Exp: 09/25/2027
Acetone Stock Solution Lot #: 2025-B Exp: 09/22/2027

Simulator	Serial Number
0.000	MP5086
Interferent	MP5087
0.050	MP5088
0.080	MP5089
0.200	MP5090

Attachments

☑ Form 41
☑ Stability Checks
☑ Calibration Certificate
☑ Optical Bench Adjustment
☑ Post-Stability Checks
☐ Flow Adjustment
☐ Form 40
☑ Other: AI Note

Notes/Suggested Service: * performed flow portion of quality checks on 1/20/2026. SLH

Additional 0.080g/210L wet stability was performed 1/27/2026. SLH 1/28/2026

Tech Correction: Added mark to box on Post Optical Bench Adjustment Stability Checks. WKP 1/29/2026

☑ **Instrument Complies with Chapter 11D-8, FAC**
☐ **Instrument Does Not Comply with Chapter 11D-8, FAC**

☑ **Return to/Place into Evidentiary Use**
☐ **Remain Out of Evidentiary Use**

☑ **Conduct an Agency Inspection Before Evidentiary Use**

Taylor Gutschow Digitally signed by Taylor Gutschow Date: 2026.02.03 12:26:03 -05'00' — **Tech Review**

Kaitlyn Spearin Digitally signed by Kaitlyn Spearin Date: 2026.02.03 13:20:31 -05'00' — **Admin Review**

Helms, William

From: Helms, William
Sent: Tuesday, December 30, 2025 10:29 AM
To: leandrahigginbotham@fdle.state.fl.us
Subject: Instrument 80-001152

I just wanted to let you know that instrument 80-001152 is being sent to you, due to the 0.08 testing outside of tolerance on multiple tests.

Thank you,

Sergeant William Helms #1572
Special Operations Supervisor
New Smyrna Beach Police Department
246 Industrial Park Avenue
New Smyrna Beach, FL 32168
Office: (386) 424-2297
Whelms@cityofnsb.com
www.cityofnsb.com

Stability Checks

0.050 g/210L

0.047 to 0.053 g/210L ✓

NEW SMYRNA BEACH PD
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-001152
01/13/2026
Software: 8100.27

Test	g/210L	Time
Air Blank	0.000	12:25
Control Test	0.051	12:26
Air Blank	0.000	12:26
Control Test	0.052	12:27
Air Blank	0.000	12:28
Control Test	0.052	12:28
Air Blank	0.000	12:29

Control Test Stats

Average	0.0517
Std Dev	0.0006
Rel Std Dev(%)	1.1175

Operator's Signature

0.080 g/210L

0.077 to 0.083 g/210L ✓

#2

NEW SMYRNA BEACH PD
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-001152
01/13/2026
Software: 8100.27

Test	g/210L	Time
Air Blank	0.000	13:10
Control Test	0.082	13:10
Air Blank	0.000	13:11
Control Test	0.082	13:12
Air Blank	0.000	13:12
Control Test	0.082	13:13
Air Blank	0.000	13:13

Control Test Stats

Average	0.0820
Std Dev	0.0000
Rel Std Dev(%)	0.0000

Operator's Signature

0.200 g/210L

0.194 to 0.206 g/210L ✓

NEW SMYRNA BEACH PD
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-001152
01/13/2026
Software: 8100.27

Test	g/210L	Time
Air Blank	0.000	12:50
Control Test	0.198	12:51
Air Blank	0.000	12:52
Control Test	0.198	12:52
Air Blank	0.000	12:53
Control Test	0.198	12:53
Air Blank	0.000	12:54

Control Test Stats

Average	0.1980
Std Dev	0.0000
Rel Std Dev(%)	0.0000

Operator's Signature

DGS 0.080 g/210L

0.077 to 0.083 g/210L ✓
≤0.003 g/210L of Wet ✓

DGS

NEW SMYRNA BEACH PD
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-001152
01/13/2026
Software: 8100.27

Test	g/210L	Time
Air Blank	0.000	12:30
Control Test	0.081	12:31
Air Blank	0.000	12:31
Control Test	0.081	12:31
Air Blank	0.000	12:32
Control Test	0.082	12:32
Air Blank	0.000	12:33

Control Test Stats

Average	0.0813
Std Dev	0.0006
Rel Std Dev(%)	0.7199

Operator's Signature

NEW SMYRNA BEACH PD
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-001152
01/13/2026
Software: 8100.27

Test	g/210L	Time
Air Blank	0.000	12:38
Control Test	0.084	12:39
Air Blank	0.000	12:40
Control Test	0.083	12:40
Air Blank	0.000	12:41
Control Test	0.082	12:42
Air Blank	0.000	12:42

Control Test Stats

Average	0.0830
Std Dev	0.0010
Rel Std Dev(%)	1.2048

Operator's Signature

re-fitted SIM / tightened and re-ran
~~sent~~
80-001152
1/13/2026

NEW SMYRNA BEACH PD
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-001152
01/27/2026
Software: 8100.27

Test	g/210L	Time
Air Blank	0.000	10:05
Control Test	0.084 *	10:06
Air Blank	0.000	10:07
Control Test	0.083	10:07
Air Blank	0.000	10:08
Control Test	0.083	10:08
Air Blank	0.000	10:09
Control Test	0.083	10:10
Air Blank	0.000	10:10
Control Test	0.083	10:11
Air Blank	0.000	10:11
Control Test	0.083	10:12
Air Blank	0.000	10:13
Control Test	0.083	10:13
Air Blank	0.000	10:14
Control Test	0.083	10:15
Air Blank	0.000	10:15
Control Test	0.083	10:16
Air Blank	0.000	10:16
Control Test	0.083	10:17
Air Blank	0.000	10:18

Control Test Stats

Average	0.0831
Std Dev	0.0003
Rel Std Dev(%)	0.3805

Operator's Signature

1/27/26 SWT

an additional wet 0.08 g/210L ~~to~~ SWT stability performed to verify accuracy again due to the agency inspector note. Based on the 10 replicates - an optical bench adjustment will be performed.

SWT

NEW SMYRNA BEACH PD
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-001152
01/27/2026 13:13:21

Auto Calibration
Max Power Res Value = 24
Auto Range Res Value = 19

Sol Value = 0.000 g/210L ***
Fit value = 0.0000 mg/l %%%%
Samples Taken = 4, Discarded = 1
3um Io = 12794, 9um Io = 13770

<<<<< CHANNEL 1 >>>>>

Sample	% Abs	(% Abs Ref)
Sample #1 =	0.1290	(-0.0180)
Sample #2 =	0.1300	(-0.0050)
Sample #3 =	0.1430	(-0.0160)
Sample #4 =	0.1370	(0.0080)

Avg % Abs = 0.1367 (-0.0043)
STD DEV = 0.0065 (0.0120)
REL STD DEV = 4.761 (277.243)

<<<<< CHANNEL 2 >>>>>

Sample	% Abs	(% Abs Ref)
Sample #1 =	0.1860	(-0.0150)
Sample #2 =	0.2090	(-0.0110)
Sample #3 =	0.2060	(-0.0210)
Sample #4 =	0.1970	(-0.0090)

Avg % Abs = 0.2040 (-0.0137)
STD DEV = 0.0062 (0.0064)
REL STD DEV = 3.061 (47.042)

Sol Value = 0.040 g/210L ***
Fit value = 0.1905 mg/l %%%%
Samples Taken = 4, Discarded = 1
3um Io = 12817, 9um Io = 13779

<<<<< CHANNEL 1 >>>>>

Sample	% Abs	(% Abs Ref)
Sample #1 =	0.8420	(0.0000)
Sample #2 =	0.8320	(0.0100)
Sample #3 =	0.8500	(0.0080)
Sample #4 =	0.8590	(0.0060)

Avg % Abs = 0.8470 (0.0080)
STD DEV = 0.0137 (0.0120)
REL STD DEV = 1.623 (25.000)

<<<<< CHANNEL 2 >>>>>

Sample	% Abs	(% Abs Ref)
Sample #1 =	1.6350	(-0.0240)
Sample #2 =	1.6060	(-0.0130)
Sample #3 =	1.6120	(-0.0060)
Sample #4 =	1.6250	(-0.0140)

Avg % Abs = 1.6110 (-0.0110)
STD DEV = 0.0123 (0.0044)
REL STD DEV = 0.763 (39.626)

Sol Value = 0.100 g/210L ***
Fit value = 0.4762 mg/l %%%%
Samples Taken = 4, Discarded = 1
3um Io = 12817, 9um Io = 13784

<<<<< CHANNEL 1 >>>>>

Sample	% Abs	(% Abs Ref)
Sample #1 =	1.9640	(-0.0220)
Sample #2 =	1.9250	(-0.0120)
Sample #3 =	1.9310	(-0.0040)
Sample #4 =	1.9210	(-0.0020)

Avg % Abs = 1.9257 (-0.0060)
STD DEV = 0.0050 (0.0053)
REL STD DEV = 0.261 (88.192)

<<<<< CHANNEL 2 >>>>>

Sample	% Abs	(% Abs Ref)
Sample #1 =	3.7430	(-0.0070)
Sample #2 =	3.7150	(0.0060)
Sample #3 =	3.7030	(0.0180)
Sample #4 =	3.7150	(-0.0060)

Avg % Abs = 3.7110 (0.0080)
STD DEV = 0.0065 (0.0269)
REL STD DEV = 0.187 (200.000)

Sol Value = 0.200 g/210L ***
Fit value = 0.9524 mg/l %%%%
Samples Taken = 4, Discarded = 1
3um Io = 12814, 9um Io = 13782

<<<<< CHANNEL 1 >>>>>

Sample	% Abs	(% Abs Ref)
Sample #1 =	3.7180	(-0.0040)
Sample #2 =	3.6760	(0.0540)
Sample #3 =	3.6750	(0.0330)
Sample #4 =	3.6610	(0.0690)

Avg % Abs = 3.6707 (0.0520)
STD DEV = 0.0084 (0.0181)
REL STD DEV = 0.228 (34.775)

<<<<< CHANNEL 2 >>>>>

Sample	% Abs	(% Abs Ref)
Sample #1 =	7.0930	(-0.0130)
Sample #2 =	7.0530	(0.0380)
Sample #3 =	7.0470	(0.0360)
Sample #4 =	7.0370	(0.0610)

Avg % Abs = 7.0473 (0.0450)
STD DEV = 0.0105 (0.0139)
REL STD DEV = 0.149 (30.872)

Sol Value = 0.300 g/210L ***
Fit value = 1.4286 mg/l %%%%
Samples Taken = 4, Discarded = 1
3um Io = 12812, 9um Io = 13762

<<<<< CHANNEL 1 >>>>>

Sample	% Abs	(% Abs Ref)
Sample #1 =	5.4160	(0.0000)
Sample #2 =	5.3650	(0.0590)
Sample #3 =	5.3490	(0.0670)
Sample #4 =	5.3330	(0.0750)

Avg % Abs = 5.3490 (0.0670)
STD DEV = 0.0160 (0.0081)
REL STD DEV = 0.299 (11.940)

<<<<< CHANNEL 2 >>>>>

Sample	% Abs	(% Abs Ref)
Sample #1 =	10.2520	(0.0030)
Sample #2 =	10.2050	(0.0830)
Sample #3 =	10.1800	(0.0910)
Sample #4 =	10.1730	(0.0980)

Avg % Abs = 10.1860 (0.0907)
STD DEV = 0.0168 (0.0075)
REL STD DEV = 0.165 (8.278)

***** AUTO CAL DATA *****

<<<<< CHANNEL 1 >>>>>

Sol Val = 0.0000 mg/l or 0.000 g/210L
% Abs = 0.137
Std Dev = 0.01 Rel Std Dev = 4.76
Sol Val = 0.1905 mg/l or 0.040 g/210L
% Abs = 0.847
Std Dev = 0.01 Rel Std Dev = 1.62
Sol Val = 0.4762 mg/l or 0.100 g/210L
% Abs = 1.926
Std Dev = 0.01 Rel Std Dev = 0.26
Sol Val = 0.9524 mg/l or 0.200 g/210L
% Abs = 3.671
Std Dev = 0.01 Rel Std Dev = 0.23
Sol Val = 1.4286 mg/l or 0.300 g/210L
% Abs = 5.349
Std Dev = 0.02 Rel Std Dev = 0.30
Zero Order Coef = -338.55
First Order Coef = 2599.38
Second Order Coef = 24.95
Standard Deviation = 16.858664

<<<<< CHANNEL 2 >>>>>

Sol Val = 0.0000 mg/l or 0.000 g/210L
% Abs = 0.204
Std Dev = 0.01 Rel Std Dev = 3.06
Sol Val = 0.1905 mg/l or 0.040 g/210L
% Abs = 1.611
Std Dev = 0.01 Rel Std Dev = 0.76
Sol Val = 0.4762 mg/l or 0.100 g/210L
% Abs = 3.711
Std Dev = 0.01 Rel Std Dev = 0.19
Sol Val = 0.9524 mg/l or 0.200 g/210L
% Abs = 7.047
Std Dev = 0.01 Rel Std Dev = 0.15
Sol Val = 1.4286 mg/l or 0.300 g/210L
% Abs = 10.186
Std Dev = 0.02 Rel Std Dev = 0.17
Zero Order Coef = -251.09
First Order Coef = 1305.86
Second Order Coef = 11.84
Standard Deviation = 15.998534

Solution Stats Quadratic Fit Chan 1

Act g/210L	Fit g/210L	Residual g/210L
0.000	0.000	-0.0004
0.040	0.040	0.0005
0.100	0.100	0.0001
0.200	0.200	-0.0003
0.300	0.300	0.0001

Solution Stats Quadratic Fit Chan 2

Act g/210L	Fit g/210L	Residual g/210L
0.000	0.000	-0.0003
0.040	0.040	0.0004
0.100	0.100	0.0001
0.200	0.200	-0.0003
0.300	0.300	0.0001

Sol Value = 0.080 g/210L ***
Fit value = 0.3810 mg/l %%%%
Samples Taken = 4, Discarded = 1
***** CHANNEL 1
Sample #1 = 3070.00
Sample #2 = 3070.00
Sample #3 = 3198.00
Sample #4 = 3202.00
Average Result = 3156.6667
STD DEV = 75.0822
REL STD DEV = 2.379
****
***** CHANNEL 2
Sample #1 = 3345.00
Sample #2 = 3356.00
Sample #3 = 3381.00
Sample #4 = 3411.00
Average Result = 3382.6667
STD DEV = 27.5379
REL STD DEV = 0.814
****
Dry Gas H2O Adjust Results **********
Barometric Pressure = 1026
3 um H2O Adjust (mg/l*10,000) = 653
9 um H2O Adjust (mg/l*10,000) = 427
**** AUTO CAL PASS

SLH

Optical Bench
Calibration
adjustment
wkp 1/27/2026

Post-Cal Stability Checks

SLH

0.05g/210L	0.08g/210L	0.20g/210L	DGS 0.08g/210L
0.047 to 0.053 ✓	*0.077 to 0.083* ✓	*0.194 to 0.206* ✓	*0.077 to 0.083* ✓ *≤0.003 of Wet* ✓

NEW SMYRNA BEACH PD
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-001152
01/27/2026
Software: 8100.27

Test	g/210L	Time
Air Blank	0.000	14:04
Control Test	0.050	14:05
Air Blank	0.000	14:05
Control Test	0.050	14:06
Air Blank	0.000	14:06
Control Test	0.049	14:07
Air Blank	0.000	14:08
Control Test Stats		
Average	0.0497	
Std Dev	0.0006	
Rel Std Dev(%)	1.1625	

Operator's Signature

NEW SMYRNA BEACH PD
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-001152
01/27/2026
Software: 8100.27

Test	g/210L	Time
Air Blank	[illegible]	14:10
Control Test	[illegible]	14:11
Air Blank	[illegible]	14:11
Control Test	[illegible]	14:12
Air Blank	[illegible]	14:13
Control Test	[illegible]	14:13
Air Blank	[illegible]	14:14
Control Test Stats		
Average	0.0803	
Std Dev	0.0006	
Rel Std Dev(%)	0.7187	

Operator's Signature

NEW SMYRNA BEACH PD
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-001152
01/27/2026
Software: 8100.27

Test	g/210L	Time
Air Blank	0.000	14:15
Control Test	0.201	14:16
Air Blank	0.000	14:17
Control Test	0.200	14:17
Air Blank	0.000	14:18
Control Test	0.200	14:18
Air Blank	0.000	14:19
Control Test Stats		
Average	0.2003	
Std Dev	0.0006	
Rel Std Dev(%)	0.2882	

Operator's Signature

NEW SMYRNA BEACH PD
Intoxilyzer - Alcohol Analyzer
Model 8000 SN 80-001152
01/27/2026
Software: 8100.27

Test	g/210L	Time
Air Blank	0.000	14:20
Control Test	0.080	14:21
Air Blank	0.000	14:21
Control Test	0.080	14:22
Air Blank	0.000	14:22
Control Test	0.079	14:22
Air Blank	0.000	14:23
Control Test Stats		
Average	0.0797	
Std Dev	0.0006	
Rel Std Dev(%)	0.7247	

Operator's Signature

Florida Department of Law Enforcement
Alcohol Testing Program

DEPARTMENT INSPECTION REPORT - INTOXILYZER 8000

Agency: NEW SMYRNA BEACH PD
Time of Inspection: 17:16
Date of Inspection: 01/27/2026
Serial Number: 80-001152
Software: 8100.27

Check or Test	YES	NO	Check or Test	YES	NO
Diagnostic Check (Pre-Inspection): OK	Yes		Date and/or Time Adjusted		No
Minimum Sample Volume Check: OK	Yes		Barometric Pressure Sensor Check: OK	Yes	
Alcohol Free Subject Test: 0.000	Yes		Mouth Alcohol Test: Slope Not Met	Yes	
Interferent Detect Test: Interferent Detect	Yes		Diagnostic Check (Post-Inspection): OK	Yes	

Alcohol Free Test (g/210L)	0.05g/210L Test (g/210L) Lot#:202406K Exp: 06/19/2026	0.08g/210L Test (g/210L) Lot#:202406L Exp: 06/19/2026	0.20g/210L Test (g/210L) Lot#:202406N Exp: 06/20/2026	0.08 g/210L Dry Gas Std Test (g/210L) Lot#:AG510701 Exp: 04/17/2027
0.000	0.048	0.077	0.195	0.079
0.000	0.047	0.077	0.194	0.080
0.000	0.047	0.077	0.195	0.080
0.000	0.046	0.077	0.194	0.080
0.000	0.046	0.076	0.195	0.080
0.000	0.046	0.076	0.195	0.080
0.000	0.045	0.077	0.194	0.080
0.000	0.046	0.076	0.194	0.080
0.000	0.046	0.076	0.194	0.080
0.000	0.046	0.076	0.195	0.080

Standard Deviations	0.0008	0.0005	0.0005	0.0003

Average Standard Deviation of 0.05, 0.08 and 0.20 g/210L Tests: 0.0005 Number of Simulators Used: 5

Remarks:

The above instrument complies (X) does not comply ( ) with Chapter 11D-8, FAC.

I certify that I performed this inspection in accordance with the provisions of Chapter 11D-8, FAC.

LEANDRA HIGGINBOTHAM
Signature and Printed Name

01/27/2026
Date

FDLE/ATP Form 41 –Revised August 2005

Calibration Certificate

Florida Department of Law Enforcement
Alcohol Testing Program
2331 Phillips Road
Tallahassee, FL 32308

This is to certify the calibration of Intoxilyzer 8000 serial number 80-001152 , manufactured by CMI, Inc. was calibrated in accordance with FDLE/ATP Form 36 - Department Inspection Procedures - Intoxilyzer 8000.

Serial Number:	80-001152
Owning Agency:	NEW SMYRNA BEACH PD
Calibration Date:	01/27/2026
Calibration Time:	17:16

	UNCERTAINTY* ±
0.050 g/ 210 L	0.004
0.080 g/ 210 L	0.004
0.200 g/ 210 L	0.008
0.080 g/ 210 L Dry Gas Control	0.005

All results are reported in g/ 210 L.
Bias is limited by calibration acceptance criteria. All calibration results must be within ± 0.005 or 5%, whichever is greater, of the target alcohol concentration.
*Uncertainty is based on fleet-wide data and is expressed to a 99.73% level of confidence (k=3).
The instrument results before and after any adjustment are found in the associated pre and post stability checks.

TRACEABILITY INFORMATION
This instrument was calibrated using solutions prepared by Alcohol Countermeasure Systems, Inc. (ACS). ACS prepared and certified these CRMs in accordance with ISO 17034 and ISO/ IEC 17025 Standards.

Simulator temperatures are traceable to NIST. Simulator temperatures are checked with NIST traceable digital thermometers calibrated by Precision Metrology in accordance with ISO/ IEC 17025 standards.

Dry gas control measurements are traceable to NIST through the use of CRMs supplied by an accredited CRM supplier. The supplier of dry gas standard controls prepared and certified the CRMs in accordance with ISO Guide 34 and ISO/ IEC 17025 standards.

01/27/2026
Date

LEANDRA HIGGINBOTHAM,
Department Inspector