INSTRUMENT PROCESSING SHEET

FDLE Florida Department of Law Enforcement

Agency **PALM BAY PD**   S/N **80-001721**

Date In **7/2/25**   DI Completion Date **07/29/2025**   ■Ship ☐P/U ☐H/D ☐CMI ☐EE

Intake   By **KTS**   Date **7/2/25**

- ■ Annual
- ☐ Registration
- ☐ Return from CMI / EE

Visual Inspection:
- ■ Case ■ Handle
- ■ Keyboard ■ Dry Gas Shelf
- ■ Feet ■ Breath Tube
- ■ Ports ■ Screws Tight

Other Equipment/ Accessories:
- ☐ Power cord ☐ Printer Cable
- ■ Static Bag ☐ 12V DC Cable

Notes: _____

_____

Quality Checks   By **WKP**   Date **7/10/2025**

- ■ Breath Tube Screen
- ■ Replace External O-Rings
- ■ Instrument Set Up Verified
- ■ R-Value **115**
- ■ Flow Verification (L/s)

Flow Column # **ATP 102**

32 mm	0.144	(.139 - .169)
36 mm	0.160	(.156 - .190)
53 mm	0.230	(.228 - .278)
103 mm	0.503	(.447 - .547)

- ■ Barometric Pressure Check

Gauge ID # **28662**

- ■ Stability Checks

Simulator	Serial #	Lot #/Exp
0.050	MP5088	202406K
		06/19/2026
0.080	MP5089	202406L
		06/19/2026
0.200	MP5090	202406N
		06/20/2026
0.080 DGS	N/A	AG429602
		10/22/2026

Flow Calibration   By _____   Date _____

Flow Column # _____
- ☐ 5L/min – 17mm
- ☐ 15L/min – 53mm
- ☐ 30L/min – 103mm
- ☐ R-Value _____
- ☐ Post Calibration Verification (L/s)

Flow Column # _____

32 mm		(.139 - .169)
36 mm		(.156 - .190)
53 mm		(.228 - .278)
103 mm		(.447 - .547)

Maintenance   By _____   Date _____

- ☐ Battery Replacement
- ☐ Dry Gas Regulator Replacement
- ☐ Breath Tube Replacement
- ☐ Other _____

Calibration Adjustment   By **SLH**

Barometric Pressure Gauge **1014**   ID # **28427**

Simulator	Serial #	Lot #	Expiration
0.000	MP6294	N/A	N/A
0.040	MP6295	24330	09/10/2026
0.100	MP6296	24390	10/29/2026
0.200	MP6297	24080	02/13/2026
0.300	MP6298	24170	05/07/2026
0.080 DGS	N/A	28424080A3	11/05/2026

■ Post Calibration Adjustment Stability Checks

Simulator	Serial #	Lot #	Expiration
0.050	MP5088	202406K	06/19/2026
0.080	MP6292	202406L	06/19/2026
0.200	MP5090	202406N	06/20/2026
0.080 DGS	N/A	AG429602	10/22/2026

Notes/Suggested Service: _____
Inadvertently ran a Dry Gas Control Test, aborted
sequence and attached print out. WKP 7/10/25
Ran post-stabilities over 2 days. SLH 7/29/2025

Department Inspection   By **SLH**

Barometric Pressure ID# **28421**

Gauge **1013**   Instrument **1010**

Mouth Alcohol Solution Lot # **2025-A**

Acetone Stock Solution Lot # **2024-B**

Simulator	Serial Number
0.000	MP6289
Interferent	MP6290
0.050	MP5088
0.080	MP5089
0.200	MP5090

Attachments

- ■ Form 41
- ■ Stability Checks
- ■ Calibration Certificate
- ■ Calibration Adjustment
- ■ Post-Stability Checks
- ☐ Flow Calibration
- ☐ Form 40
- ■ Other **Dry Gas Control**

- ■ **Instrument Complies with Chapter 11D-8, FAC**
- ☐ **Instrument Does Not Comply with Chapter 11D-8, FAC**
- ■ **Return to/Place into Evidentiary Use**
- ☐ **Remain Out of Evidentiary Use**
- ■ **Conduct an Agency Inspection Before Evidentiary Use**

Taylor Gutschow
Digitally signed by Taylor Gutschow
Date: 2025.07.31 13:37:27 -04'00'
Tech Review / Date

Shayla Platt
Digitally signed by Shayla Platt
Date: 2025.08.07 08:19:52 -04'00'
Admin Review / Date

Stability Checks

0.05g/210L		0.08g/210L		0.20g/210L		DGS 0.08g/210L		
0.047 to 0.053	✓	0.077 to 0.083	✓	0.194 to 0.206	✓	0.077 to 0.083	≤0.003 of Wet	✓
Performed Root Case Analysis		*Performed Root Case Analysis*		*Performed Root Case Analysis*		*Performed Root Case Analysis*		

```
PALM BAY PD
Intoxilyzer - Alcohol Analyzer
Model: 8000          SN 80-001721
07/10/2025
Software: 8100.27

Test          g/210L        Time
-------------------------------
Air Blank     0.000        11:03
Control Test  0.050        11:04
Air Blank     0.000        11:04
Control Test  0.050        11:05
Air Blank     0.000        11:05
Control Test  0.050        11:06
Air Blank     0.000        11:07
Control Test Stats
  Average      0.0500
  Std Dev      0.0000
  Rel Std Dev(%) 0.0000
```

```
PALM BAY PD
Intoxilyzer - Alcohol Analyzer
Model: 8000          SN 80-001721
07/10/2025
Software: 8100.27

Test          g/210L        Time
-------------------------------
Air Blank     0.000        11:11
Control Test  0.079        11:11
Air Blank     0.000        11:12
Control Test  0.079        11:12
Air Blank     0.000        11:13
Control Test  0.080        11:14
Air Blank     0.000        11:14
Control Test Stats
  Average      0.0793
  Std Dev      0.0006
  Rel Std Dev(%) 0.7277
```

```
PALM BAY PD
Intoxilyzer - Alcohol Analyzer
Model: 8000          SN 80-001721
07/10/2025
Software: 8100.27

Test          g/210L        Time
-------------------------------
Air Blank     0.000        11:18
Control Test  0.198        11:18
Air Blank     0.000        11:19
Control Test  0.198        11:20
Air Blank     0.000        11:20
Control Test  0.198        11:21
Air Blank     0.000        11:21
Control Test Stats
  Average      0.1980
  Std Dev      0.0000
  Rel Std Dev(%) 0.0000
```

```
PALM BAY PD
Intoxilyzer - Alcohol Analyzer
Model: 8000          SN 80-001721
07/10/2025
Software: 8100.27

Test          g/210L        Time
-------------------------------
Air Blank     0.000        10:49
Control Test  0.069        10:50
Air Blank     0.000        10:50
Control Test  0.071        10:51
Air Blank     0.000        10:51
Control Test  0.073        10:51
Air Blank     0.000        10:52
Control Test Stats
  Average      0.0710
  Std Dev      0.0021
  Rel Std Dev(%) 2.8169
```

_____
Operator's Signature

_____
Operator's Signature

_____
Operator's Signature

_____
Operator's Signature

PALM BAY PD
Intoxilyzer - Alcohol Analyzer
Model 8000   SN 80-001721
07/10/2025
Software: 8100.27

Test	g/210L	Time
Air Blank	0.000	10:38
Control Test	0.169	10:39
Air Blank	0.000	10:39
Control Test	0.168	10:40
Air Blank	0.000	11:40
Control Test	0.070	10:40
Air Blank	0.000	10:41
Control Test Stats		
Average	0.1691	
Std Dev	0.0010	
Rel Std Dev(%)	1.4493	

_____
Operator's Signature

0.08g/210L
   DOJS STABILITY
   CHECK #1

○ Performed RCA
  repeated test

Inadvertently
prompted Dry
Control Test

```
Palm Bay PD
Intoxilyzer - Alcohol Analyzer
Model 8000            SN 80-001721
17/10/2025
Software: 8100.27

          --------------------
          : DRY CONTROL TEST :
          --------------------

Test            g/210L           Time
--------------------------------------
Air Blank       ABT*             11:07
Air Blank       0.000            11:18

*Sequence Aborted




_____
         Operator's Signature
```

```
PALM BAY PD
Intoxilyzer - Alcohol Analyzer
Model 8000              SN 80-001721
07/28/2025              10:40:15

Auto Calibration
Max Power Res Value = 29
Auto Range Res Value = 17

Sol Value = 0.000 g/210L ***
Fit value = 0.0000 mg/l %%%%
Samples Taken = 4, Discarded = 1
3um Io = 12829, 9um Io = 12204
      <<<<< CHANNEL 1 >>>>>
  Sample      % Abs     (% Abs Ref)
Sample #1 =  0.1490     (0.0080)
Sample #2 =  0.1230     (0.0560)
Sample #3 =  0.1240     (0.0720)
Sample #4 =  0.1320     (0.1090)
Avg % Abs = 0.1263  (0.0790)
STD DEV = 0.0049  (0.0272)
REL STD DEV = 3.905  (34.411)
       ------------------

      <<<<< CHANNEL 2 >>>>>
  Sample      % Abs     (% Abs Ref)
Sample #1 =  0.1520     (0.0110)
Sample #2 =  0.1480     (0.0340)
Sample #3 =  0.1400     (0.0400)
Sample #4 =  0.1240     (0.0720)
Avg % Abs = 0.1373  (0.0487)
STD DEV = 0.0122  (0.0204)
REL STD DEV = 8.898  (41.977)
       ------------------

Sol Value = 0.040 g/210L ***
Fit value = 0.1905 mg/l %%%%
Samples Taken = 4, Discarded = 1
3um Io = 12805, 9um Io = 12189
      <<<<< CHANNEL 1 >>>>>
  Sample      % Abs     (% Abs Ref)
Sample #1 =  0.8460     (-0.0110)
Sample #2 =  0.8520     (0.0220)
Sample #3 =  0.8540     (0.0360)
Sample #4 =  0.8610     (0.0600)
Avg % Abs = 0.8557  (0.0393)
STD DEV = 0.0047  (0.0192)
REL STD DEV = 0.552  (48.859)
       ------------------

      <<<<< CHANNEL 2 >>>>>
  Sample      % Abs     (% Abs Ref)
Sample #1 =  1.5200     (-0.0270)
Sample #2 =  1.5690     (-0.0270)
Sample #3 =  1.5120     (0.0050)
Sample #4 =  1.5350     (0.0070)
Avg % Abs = 1.5387  (-0.0050)
STD DEV = 0.0287  (0.0191)
REL STD DEV = 1.864  (381.576)
       ------------------
```

```
Sol Value = 0.100 g/210L ***
Fit value = 0.4762 mg/l %%%%
Samples Taken = 4, Discarded = 1
3um Io = 12778, 9um Io = 12174
      <<<<< CHANNEL 1 >>>>>
  Sample      % Abs     (% Abs Ref)
Sample #1 =  1.9350     (-0.0100)
Sample #2 =  1.8990     (0.0260)
Sample #3 =  1.9260     (0.0140)
Sample #4 =  1.8790     (0.0610)
Avg % Abs = 1.9013  (0.0337)
STD DEV = 0.0236  (0.0244)
REL STD DEV = 1.241  (72.534)
       ------------------

      <<<<< CHANNEL 2 >>>>>
  Sample      % Abs     (% Abs Ref)
Sample #1 =  3.5620     (-0.0090)
Sample #2 =  3.5310     (-0.0050)
Sample #3 =  3.5500     (-0.0160)
Sample #4 =  3.5290     (0.0030)
Avg % Abs = 3.5367  (-0.0060)
STD DEV = 0.0116  (0.0095)
REL STD DEV = 0.328  (158.990)
       ------------------

Sol Value = 0.200 g/210L ***
Fit value = 0.9524 mg/l %%%%
Samples Taken = 4, Discarded = 1
3um Io = 12771, 9um Io = 12173
      <<<<< CHANNEL 1 >>>>>
  Sample      % Abs     (% Abs Ref)
Sample #1 =  3.6510     (0.0070)
Sample #2 =  3.6540     (0.0180)
Sample #3 =  3.6210     (0.0350)
Sample #4 =  3.6370     (0.0600)
Avg % Abs = 3.6373  (0.0377)
STD DEV = 0.0165  (0.0211)
REL STD DEV = 0.454  (56.088)
       ------------------

      <<<<< CHANNEL 2 >>>>>
  Sample      % Abs     (% Abs Ref)
Sample #1 =  6.7460     (0.0080)
Sample #2 =  6.7950     (-0.0080)
Sample #3 =  6.7540     (0.0000)
Sample #4 =  6.7630     (0.0160)
Avg % Abs = 6.7707  (0.0027)
STD DEV = 0.0215  (0.0122)
REL STD DEV = 0.318  (458.258)
       ------------------

Sol Value = 0.300 g/210L ***
Fit value = 1.4286 mg/l %%%%
Samples Taken = 4, Discarded = 1
3um Io = 12762, 9um Io = 12171
      <<<<< CHANNEL 1 >>>>>
  Sample      % Abs     (% Abs Ref)
Sample #1 =  5.3070     (-0.0140)
Sample #2 =  5.3210     (0.0220)
Sample #3 =  5.3080     (0.0430)
Sample #4 =  5.3110     (0.0250)
Avg % Abs = 5.3133  (0.0300)
STD DEV = 0.0068  (0.0114)
REL STD DEV = 0.128  (37.859)
       ------------------
```

```
      <<<<< CHANNEL 2 >>>>>
  Sample      % Abs     (% Abs Ref)
Sample #1 =  9.7920     (0.0010)
Sample #2 =  9.8010     (0.0220)
Sample #3 =  9.8150     (0.0330)
Sample #4 =  9.8010     (0.0250)
Avg % Abs = 9.8057  (0.0267)
STD DEV = 0.0081  (0.0057)
REL STD DEV = 0.082  (21.323)
       ------------------


***** AUTO CAL DATA *****
      <<<<< CHANNEL 1 >>>>>
Sol Val = 0.0000 mg/l or 0.000 g/210L
  % Abs =   0.126
  Std Dev =  0.00 Rel Std Dev =  3.90
Sol Val = 0.1905 mg/l or 0.040 g/210L
  % Abs =   0.856
  Std Dev =  0.00 Rel Std Dev =  0.55
Sol Val = 0.4762 mg/l or 0.100 g/210L
  % Abs =   1.901
  Std Dev =  0.02 Rel Std Dev =  1.24
Sol Val = 0.9524 mg/l or 0.200 g/210L
  % Abs =   3.637
  Std Dev =  0.02 Rel Std Dev =  0.45
Sol Val = 1.4286 mg/l or 0.300 g/210L
  % Abs =   5.313
  Std Dev =  0.01 Rel Std Dev =  0.13
Zero Order Coef = -341.41
First Order Coef = 2630.70
Second Order Coef = 22.94
Standard Deviation = 15.324927
       ------------------

      <<<<< CHANNEL 2 >>>>>
Sol Val = 0.0000 mg/l or 0.000 g/210L
  % Abs =   0.137
  Std Dev =  0.01 Rel Std Dev =  8.90
Sol Val = 0.1905 mg/l or 0.040 g/210L
  % Abs =   1.539
  Std Dev =  0.03 Rel Std Dev =  1.86
Sol Val = 0.4762 mg/l or 0.100 g/210L
  % Abs =   3.537
  Std Dev =  0.01 Rel Std Dev =  0.33
Sol Val = 0.9524 mg/l or 0.200 g/210L
  % Abs =   6.771
  Std Dev =  0.02 Rel Std Dev =  0.32
Sol Val = 1.4286 mg/l or 0.300 g/210L
  % Abs =   9.806
  Std Dev =  0.01 Rel Std Dev =  0.08
Zero Order Coef = -188.00
First Order Coef = 1348.36
Second Order Coef = 12.98
Standard Deviation = 13.184261
       ------------------
```

Solution Stats Quadratic Fit Chan 1		
Act	Fit	Residual
g/210L	g/210L	g/210L
0.000	-0.000	0.0002
0.040	0.040	-0.0005
0.100	0.100	0.0004
0.200	0.200	-0.0001
0.300	0.300	0.0000

```
------------------------------------
| Solution Stats Quadratic Fit Chan 2 |
| Act      Fit      Residual         |
| g/210L   g/210L   g/210L           |
| 0.000   -0.000    0.0001           |
| 0.040    0.040   -0.0003           |
| 0.100    0.100    0.0004           |
| 0.200    0.200   -0.0003           |
| 0.300    0.300    0.0001           |
------------------------------------
```

Sol Value = 0.080 g/210L ***
Fit value = 0.3810 mg/l %%%%
Samples Taken = 4, Discarded = 1
***** CHANNEL 1
Sample #1 = 2530.00
Sample #2 = 2636.00
Sample #3 = 2721.00
Sample #4 = 2883.00
Average Result = 2746.6667
STD DEV = 125.4844
REL STD DEV = 4.569
****
***** CHANNEL 2
Sample #1 = 2875.00
Sample #2 = 3103.00
Sample #3 = 3057.00
Sample #4 = 3165.00
Average Result = 3108.3333
STD DEV = 54.1972
REL STD DEV = 1.744
****
Sol Value = 0.080 g/210L ***
Fit value = 0.3810 mg/l %%%%
Samples Taken = 4, Discarded = 1
***** CHANNEL 1
Sample #1 = 2792.00
Sample #2 = 2896.00
Sample #3 = 2969.00
Sample #4 = 2850.00
Average Result = 2905.0000
STD DEV = 60.0083
REL STD DEV = 2.066
****
***** CHANNEL 2
Sample #1 = 3151.00
Sample #2 = 3195.00
Sample #3 = 3245.00
Sample #4 = 3266.00
Average Result = 3235.3333
STD DEV = 36.4737
REL STD DEV = 1.127
****
Dry Gas H20 Adjust Results **********
  Barometric Pressure = 1014
  3 um H20 Adjust (mg/l*10,000) = 904
  9 um H20 Adjust (mg/l*10,000) = 574
**** AUTO CAL PASS

Post stability

DgS

PALM BAY PD
Intoxilyzer - Alcohol Analyzer
Model 8000   SN 80-001721
07/28/2025
Software: 8100.27

Test	g/210L	Time
Air Blank	0.000	11:44
Control Test	0.000	11:44
Air Blank	0.000	11:44
Control Test	0.000	11:45
Air Blank	0.000	11:45
Control Test	0.000	11:46
Air Blank	0.000	11:46
Control Test Stats		
Average	0.0000	
Std Dev	0.0000	
Rel Std Dev(%)	0.0000	

_____
Operator's Signature

RCA -
gas cylinder was empty -
Reran with new cylinder
Stt
7/28/25

Post-Calibration Adjustment Stability Checks

0.050 g/210L	0.080 g/210L	0.200 g/210L	DGS 0.080 g/210L
0.047 to 0.053 g/210L	0.077 to 0.083 g/210L	0.194 to 0.206 g/210L	0.077 to 0.083 g/210L ≤0.003 g/210L of Wet
Performed Root Case Analysis	Performed Root Case Analysis	Performed Root Case Analysis	Performed Root Case Analysis

0.050 g/210L

```
PALM BAY PD
Intoxilyzer - Alcohol Analyzer
Model 8000          SN 80-001721
07/29/2025
Software: 8100.27

Test              g/210L    Time
Air Blank          0.000    09:37
Control Test       0.049    09:38
Air Blank          0.000    09:39
Control Test       0.050    09:39
Air Blank          0.000    09:40
Control Test       0.049    09:40
Air Blank          0.000    09:41
Control Test Stats
Average            0.0493
Std Dev            0.0006
Rel Std Dev(%)     1.1703
```

Operator's Signature

0.080 g/210L

```
PALM BAY PD
Intoxilyzer - Alcohol Analyzer
Model 8000          SN 80-001721
07/28/2025
Software: 8100.27

Test              g/210L    Time
Air Blank          0.000    11:58
Control Test       0.081    11:58
Air Blank          0.000    11:59
Control Test       0.080    11:59
Air Blank          0.000    12:00
Control Test       0.080    12:01
Air Blank          0.000    12:01
Control Test Stats
Average            0.0803
Std Dev            0.0006
Rel Std Dev(%)     0.7187
```

Operator's Signature

0.200 g/210L

```
PALM BAY PD
Intoxilyzer - Alcohol Analyzer
Model 8000          SN 80-001721
07/29/2025
Software: 8100.27

Test              g/210L    Time
Air Blank          0.000    09:32
Control Test       0.198    09:33
Air Blank          0.000    09:33
Control Test       0.197    09:34
Air Blank          0.000    09:34
Control Test       0.198    09:35
Air Blank          0.000    09:36
Control Test Stats
Average            0.1977
Std Dev            0.006
Rel Std Dev(%)     0.2921
```

Operator's Signature

DGS 0.080 g/210L

DGS #2

```
PALM BAY PD
Intoxilyzer - Alcohol Analyzer
Model 8000          SN 80-001721
07/28/2025
Software: 8100.27

Test              g/210L    Time
Air Blank          0.000    11:49
Control Test       0.079    11:49
Air Blank          0.000    11:50
Control Test       0.078    11:50
Air Blank          0.000    11:51
Control Test       0.079    11:51
Air Blank          0.000    11:52
Control Test Stats
Average            0.0787
Std Dev            0.0006
Rel Std Dev(%)     0.7339
```

Operator's Signature

Florida Department of Law Enforcement
Alcohol Testing Program

DEPARTMENT INSPECTION REPORT - INTOXILYZER 8000

Agency: PALM BAY PD
Time of Inspection: 17:47   Date of Inspection: 07/29/2025

Serial Number: 80-001721
Software: 8100.27

Check or Test	YES	NO	Check or Test	YES	NO
Diagnostic Check (Pre-Inspection): OK	Yes		Date and/or Time Adjusted		No
Minimum Sample Volume Check: OK	Yes		Barometric Pressure Sensor Check: OK	Yes	
Alcohol Free Subject Test: 0.000	Yes		Mouth Alcohol Test: Slope Not Met	Yes	
Interferent Detect Test: Interferent Detect	Yes		Diagnostic Check (Post-Inspection): OK	Yes	

Alcohol Free Test (g/210L)	0.05g/210L Test (g/210L) Lot#:202406K Exp: 06/19/2026	0.08g/210L Test (g/210L) Lot#:202406L Exp: 06/19/2026	0.20g/210L Test (g/210L) Lot#:202406N Exp: 06/20/2026	0.08 g/210L Dry Gas Std Test (g/210L) Lot#:AG429602 Exp: 10/22/2026
0.000	0.048	0.078	0.195	0.073 / 0.080
0.000	0.048	0.078	0.196	0.077 / 0.081
0.000	0.048	0.078	0.196	0.079 / 0.081
0.000	0.048	0.078	0.196	0.079 / 0.081
0.000	0.048	0.078	0.197	0.080 / 0.081
0.000	0.048	0.079	0.196	0.080 / 0.081
0.000	0.049	0.079	0.196	0.081 / 0.081
0.000	0.049	0.079	0.196	0.080 / 0.081
0.000	0.049	0.079	0.197	0.081 / 0.081
0.000	0.048	0.079	0.196	0.081 / 0.081

Standard Deviations	0.0004	0.0005	0.0005	0.0024 / 0.0003

Average Standard Deviation of 0.05, 0.08 and 0.20 g/210L Tests: 0.0004   Number of Simulators Used: 5

Remarks:
 08: Control Outside Tolerance.TIGHTENED CYLINDER, RERAN   *SLH*

The above instrument complies (X) does not comply ( ) with Chapter 11D-8, FAC.

I certify that I performed this inspection in accordance with the provisions of Chapter 11D-8, FAC.

_____   LEANDRA HIGGINBOTHAM
Signature and Printed Name

07/29/2025
Date

FDLE/ATP Form 41 –Revised August 2005

Calibration Certificate

Florida Department of Law Enforcement
Alcohol Testing Program
2331 Phillips Road
Tallahassee, FL 32308

This is to certify the calibration of Intoxilyzer 8000 serial number 80-001721 ; manufactured by CMI, Inc. was calibrated in accordance with FDLE/ATP Form 36 - Department Inspection Procedures - Intoxilyzer 8000.

		UNCERTAINTY* ±
Serial Number:	80-001721	
Owning Agency:	PALM BAY PD	
Calibration Date:	07/29/2025	
Calibration Time:	17:47	
	0.050 g / 210 L	0.004
	0.080 g / 210 L	0.004
	0.200 g / 210 L	0.007
	0.080 g / 210 L Dry Gas Control	0.005

All results are reported in g/ 210 L.
Bias is limited by calibration acceptance criteria. All calibration results must be within ± 0.005 or 5%, whichever is greater, of the target alcohol concentration.
*Uncertainty is based on fleet-wide data and is expressed to a 99.73% level of confidence (k=3).
The instrument results before and after any adjustment are found in the associated pre and post stability checks.

TRACEABILITY INFORMATION
This instrument was calibrated using solutions prepared by Alcohol Countermeasure Systems, Inc. (ACS). ACS prepared and certified these CRMs in accordance with ISO 17034 and ISO/ IEC 17025 Standards.

Simulator temperatures are traceable to NIST. Simulator temperatures are checked with NIST traceable digital thermometers calibrated by Precision Metrology in accordance with ISO/ IEC 17025 standards.

Dry gas control measurements are traceable to NIST through the use of CRMs supplied by an accredited CRM supplier. The supplier of dry gas standard controls prepared and certified the CRMs in accordance with ISO Guide 34 and ISO /IEC 17025 standards.
This document shall not be reproduced except in full, without written approval of the Florida Department of Law Enforcement Alcohol Testing Program.

LEANDRA HIGGINBOTHAM,
Department Inspector

07/29/2025
Date

Page 1 of 1

FDLE/ATP Form 69 October 2024
Issuing Authority: Alcohol Testing Program

Service ∗ Integrity ∗ Respect ∗ Quality