

Alcohol Testing Program - Instrument Processing Sheet

Agency: DELAND PD Instrument Serial Number: 80-001136

Date In: 8/7/2026 DI Completion Date: 8/13/2026 ☒ Ship ☐ P/U ☐ H/D ☐ CMI ☐ EE

Intake By: <u>WKP</u> Date: <u>8/11/2026</u>		Quality Checks By: <u>SLH</u> Date: <u>8/11/2026</u>		Flow Adjustment By: _____																															
☒ Annual ☐ Dropped Off ☐ Registration ☐ Return from CMI / EE ☐ Training Instrument Visual Inspection ☒ Case ☒ Handle ☒ Keyboard ☒ Dry Gas Shelf ☒ Feet ☒ Breath Tube ☒ Ports ☒ Screws Tight Other Equipment/Accessories ☐ Power Cord ☐ Printer Cable ☐ Static Bag ☐ 12V DC Cable Notes:		☒ Breath Tube Screen ☒ Replace External O-Rings ☒ Instrument Set Up Verified ☒ R-Value: <u>207</u> ☒ Flow Verification (L/s) Flow Column #: <u>ATP 105</u> 32 mm 0.164 (.139-.169) 36 mm 0.187 (.156-.190) 53 mm 0.257 (.228-.278) 103 mm 0.539 (.447-.547) ☒ Barometric Pressure Check Gauge ID #: <u>28427</u> Gauge: <u>1013</u> Instrument: <u>1013</u> ☒ Stability Checks		Flow Column #: _____ ☐ 5L/min – 17mm ☐ 15L/min – 53mm ☐ 30L/min – 103mm ☐ R-Value: _____ ☐ Post Adjustment Verification (L/S) Flow Column #: _____ 32 mm (.139-.169) 36 mm (.156-.190) 53 mm (.228-.278) 103 mm (.447-.547)																															
						<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">Simulator</th> <th style="width: 20%;">Serial #</th> <th style="width: 25%;">Lot#/Exp</th> <th style="width: 40%;">Maintenance By: _____ Date: _____</th> </tr> </thead> <tbody> <tr> <td rowspan="2">0.050</td> <td rowspan="2">MP6291</td> <td>202603A</td> <td>☐ Battery Replacement</td> </tr> <tr> <td>03/03/2028</td> <td>☐ Dry Gas Regulator Replacement</td> </tr> <tr> <td rowspan="2">0.080</td> <td rowspan="2">MP6292</td> <td>202603B</td> <td>☐ Tank Sensor Tare</td> </tr> <tr> <td>03/03/2028</td> <td>☐ Breath Tube Replacement</td> </tr> <tr> <td rowspan="2">0.200</td> <td rowspan="2">MP6293</td> <td>202603D</td> <td>☐ Other:</td> </tr> <tr> <td>03/04/2028</td> <td></td> </tr> <tr> <td rowspan="2">0.080 DGS</td> <td rowspan="2">N/A</td> <td>23825080A1</td> <td></td> </tr> <tr> <td>10/05/2027</td> <td></td> </tr> </tbody> </table>		Simulator	Serial #	Lot#/Exp	Maintenance By: _____ Date: _____	0.050	MP6291	202603A	☐ Battery Replacement	03/03/2028	☐ Dry Gas Regulator Replacement	0.080	MP6292	202603B	☐ Tank Sensor Tare	03/03/2028	☐ Breath Tube Replacement	0.200	MP6293	202603D	☐ Other:	03/04/2028		0.080 DGS	N/A	23825080A1		10/05/2027	
						Simulator	Serial #	Lot#/Exp	Maintenance By: _____ Date: _____																										
						0.050	MP6291	202603A	☐ Battery Replacement																										
								03/03/2028	☐ Dry Gas Regulator Replacement																										
0.080	MP6292	202603B	☐ Tank Sensor Tare																																
		03/03/2028	☐ Breath Tube Replacement																																
0.200	MP6293	202603D	☐ Other:																																
		03/04/2028																																	
0.080 DGS	N/A	23825080A1																																	
		10/05/2027																																	
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">Simulator</th> <th style="width: 20%;">Serial #</th> <th style="width: 25%;">Lot #</th> <th style="width: 40%;">Expiration</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td></td> <td>N/A</td> <td>N/A</td> </tr> <tr> <td>0.040</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.100</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.200</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.300</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.080 DGS</td> <td>N/A</td> <td></td> <td></td> </tr> </tbody> </table>		Simulator	Serial #	Lot #	Expiration	0.000		N/A	N/A	0.040				0.100				0.200				0.300				0.080 DGS	N/A			Department Inspection By: <u>SLH</u> Barometric Pressure Gauge: _____ ID#: _____ Barometric Pressure ID#: <u>28427</u> Gauge: <u>1012</u> Instrument: <u>1013</u> Mouth Alcohol Solution Lot #: <u>2025-D</u> Exp: <u>09/25/2027</u> Acetone Stock Solution Lot #: <u>2025-B</u> Exp: <u>09/22/2027</u>					
Simulator	Serial #	Lot #	Expiration																																
0.000		N/A	N/A																																
0.040																																			
0.100																																			
0.200																																			
0.300																																			
0.080 DGS	N/A																																		
☐ Post Optical Bench Adjustment Stability Checks		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">Simulator</th> <th style="width: 20%;">Serial #</th> <th style="width: 25%;">Lot #</th> <th style="width: 40%;">Expiration</th> </tr> </thead> <tbody> <tr> <td>0.050</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.080</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.200</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.080 DGS</td> <td>N/A</td> <td></td> <td></td> </tr> </tbody> </table>		Simulator	Serial #	Lot #	Expiration	0.050				0.080				0.200				0.080 DGS	N/A			<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">Attachments</th> <th style="width: 50%;"></th> </tr> </thead> <tbody> <tr> <td>☒ Form 41</td> <td>☐ Post-Stability Checks</td> </tr> <tr> <td>☒ Stability Checks</td> <td>☐ Flow Adjustment</td> </tr> <tr> <td>☒ Calibration Certificate</td> <td>☐ Form 40</td> </tr> <tr> <td>☐ Optical Bench Adjustment</td> <td>☒ Other: Calculation form</td> </tr> </tbody> </table>		Attachments		☒ Form 41	☐ Post-Stability Checks	☒ Stability Checks	☐ Flow Adjustment	☒ Calibration Certificate	☐ Form 40	☐ Optical Bench Adjustment	☒ Other: Calculation form
Simulator	Serial #	Lot #	Expiration																																
0.050																																			
0.080																																			
0.200																																			
0.080 DGS	N/A																																		
Attachments																																			
☒ Form 41	☐ Post-Stability Checks																																		
☒ Stability Checks	☐ Flow Adjustment																																		
☒ Calibration Certificate	☐ Form 40																																		
☐ Optical Bench Adjustment	☒ Other: Calculation form																																		
Notes/Suggested Service:		☒ Instrument Complies with Chapter 11D-8, FAC ☐ Instrument Does Not Comply with Chapter 11D-8, FAC ☒ Return to/Place into Evidentiary Use ☐ Remain Out of Evidentiary Use ☒ Conduct an Agency Inspection Before Evidentiary Use																																	
		<table style="width: 100%;"> <tr> <td style="width: 50%; text-align: center;"> Wen-Chi Pierson Digitally signed by Wen-Chi Pierson Date: 2026.08.20 08:35:13 -04'00' </td> <td style="width: 50%; text-align: center;"> Kaitlyn Spearin Digitally signed by Kaitlyn Spearin Date: 2026.08.20 12:55:42 -04'00' </td> </tr> </table>		Wen-Chi Pierson Digitally signed by Wen-Chi Pierson Date: 2026.08.20 08:35:13 -04'00'	Kaitlyn Spearin Digitally signed by Kaitlyn Spearin Date: 2026.08.20 12:55:42 -04'00'																														
		Wen-Chi Pierson Digitally signed by Wen-Chi Pierson Date: 2026.08.20 08:35:13 -04'00'	Kaitlyn Spearin Digitally signed by Kaitlyn Spearin Date: 2026.08.20 12:55:42 -04'00'																																
<table style="width: 100%;"> <tr> <td style="width: 50%; text-align: center;">Tech Review</td> <td style="width: 50%; text-align: center;">Admin Review</td> </tr> </table>		Tech Review	Admin Review																																
Tech Review	Admin Review																																		

Stability Checks

80-00 1136

0.050 g/210L	0.080 g/210L	0.200 g/210L	DGS 0.080 g/210L
0.047 to 0.053 g/210L DELAND PC Intoxilyzer - Alcohol Analyzer Model 8000 08/12/2026 Software: 8100.27 SN 80-001136 Test g/210L Time Air Blank 0.000 11:35 Control Test 0.143 11:37 Air Blank 0.007 11:37 Control Test 0.048 11:38 Air Blank 0.000 11:38 Control Test 0.148 11:39 Air Blank 0.000 11:40 Control Test Stats Average 0.0480 Std Dev 0.0000 Rel Std Dev(%) 0.0000 <i>Miguel</i> Operator's Signature	0.077 to 0.083 g/210L DELAND PC Intoxilyzer - Alcohol Analyzer Model 8000 08/12/2026 Software: 8100.27 SN 80-001136 Test g/210L Time Air Blank 0.000 12:00 Control Test 0.077 12:01 Air Blank 0.000 12:01 Control Test 0.077 12:02 Air Blank 0.000 12:02 Control Test 0.077 12:03 Air Blank 0.000 12:04 Control Test Stats Average 0.0770 Std Dev 0.0000 Rel Std Dev(%) 0.0000 <i>Miguel</i> Operator's Signature	0.194 to 0.206 g/210L DELAND PC Intoxilyzer - Alcohol Analyzer Model 8000 08/12/2026 Software: 8100.27 SN 80-001136 Test g/210L Time Air Blank 0.007 12:06 Control Test 0.199 12:06 Air Blank 0.000 12:07 Control Test 0.198 12:08 Air Blank 0.000 12:08 Control Test 0.197 12:09 Air Blank 0.000 12:09 Control Test Stats Average 0.1960 Std Dev 0.0010 Rel Std Dev(%) 0.5051 <i>Miguel</i> Operator's Signature	0.077 to 0.083 g/210L 50.003 g/210L of Wet DELAND PC Intoxilyzer - Alcohol Analyzer Model 8000 08/11/2026 Software: 8100.27 SN 80-001136 Test g/210L Time Air Blank 0.000 16:14 Control Test 0.079 16:14 Air Blank 0.000 16:15 Control Test 0.078 16:15 Air Blank 0.000 16:15 Control Test 0.079 16:16 Air Blank 0.000 16:16 Control Test Stats Average 0.0787 Std Dev 0.0006 Rel Std Dev(%) 0.7339 <i>Miguel</i> Operator's Signature

Verified instrument was able to read gas pressure.

performed 8/11/2026
Sub

Florida Department of Law Enforcement Alcohol Testing Program

DEPARTMENT INSPECTION REPORT - INTOXILYZER 8000

Agency: DELAND PD
Time of Inspection: 16:18

Date of Inspection: 08/13/2026

Serial Number: 80-001136
Software: 8100.27

Check or Test	YES	NO	Check or Test	YES	NO
Diagnostic Check (Pre-Inspection): OK	Yes		Date and/or Time Adjusted		No
Minimum Sample Volume Check: OK	Yes		Barometric Pressure Sensor Check: OK	Yes	
Alcohol Free Subject Test: 0.000	Yes		Mouth Alcohol Test: Slope Not Met	Yes	
Interferent Detect Test: Interferent Detect	Yes		Diagnostic Check (Post-Inspection): OK	Yes	

Alcohol Free Test (g/210L)	0.05g/210L Test (g/210L) Lot#:202603A Exp: 03/03/2028	0.08g/210L Test (g/210L) Lot#:202603B Exp: 03/03/2028	0.20g/210L Test (g/210L) Lot#:202603D Exp: 03/04/2028	0.08 g/210L Dry Gas Std Test (g/210L) Lot#:23725080A1 Exp: 10/05/2027
0.000	0.049	0.077	0.199	0.078
0.000	0.049	0.077	0.198	0.077
0.000	0.048	0.077	0.199	0.077
0.000	0.048	0.077	0.199	0.078
0.000	0.048	0.077	0.199	0.077
0.000	0.048	0.077	0.199	0.077
0.000	0.049	0.077	0.199	0.078
0.000	0.048	0.077	0.199	0.077
0.000	0.048	0.077	0.199	0.077
0.000	0.049	0.077	0.199	0.077

Standard Deviations	0.0005	0.0000	0.0003	0.0004
---------------------	--------	--------	--------	--------

Average Standard Deviation of 0.05, 0.08 and 0.20 g/210L Tests: 0.0003 Number of Simulators Used: 5

Remarks:

The above instrument complies (X) does not comply () with Chapter 11D-8, FAC.

I certify that I performed this inspection in accordance with the provisions of Chapter 11D-8, FAC.


LEANDRA HIGGINBOTHAM
Signature and Printed Name

08/13/2026
Date

Florida Department of Law Enforcement
Alcohol Testing Program - Average Calculations for Calibration Certificate

Calculations By: SLH

Serial Number: 80-001136

Date: 8/17/2026

Solution:

0.05 g/210 L Test: 0.484 / 10 = 0.048 g/210L
(SUM) (AVERAGE)

0.08 g/210L Test: 0.770 / 10 = 0.077 g/210L
(SUM) (AVERAGE)

0.20 g/210L Test: 1.989 / 10 = 0.199 g/210L
(SUM) (AVERAGE)

0.08 g/210L Dry Gas Std Test: 0.773 / 10 = 0.077 g/210L
(SUM) (AVERAGE)

Comments:

Average = (Sum of observations) / (Total number of observations)

All results are reported in g/210L



Calibration Certificate

Florida Department of Law Enforcement
Alcohol Testing Program
2331 Phillips Road
Tallahassee, FL 32308

This is to certify the calibration of Intoxilyzer 8000 serial number 80-001136, manufactured by CMI, Inc. was calibrated in accordance with FDLE/ATP Form 36 - Department Inspection Procedures - Intoxilyzer 8000.

Serial Number:	<u>80-001136</u>	Average of $y \pm$ Uncertainty*
Owning Agency:	<u>DELAND PD</u>	0.048 g/ 210 L 0.004
Calibration Date:	<u>08/13/2026</u>	0.077 g/ 210 L 0.004
Calibration Time:	<u>16:18</u>	0.199 g/ 210 L 0.008
		0.077 g/ 210 L Dry Gas Control 0.005

All results are reported in g/210 L.

Bias is limited by calibration acceptance criteria. All calibration results must be within ± 0.005 or 5%, whichever is greater, of the target alcohol concentration.

*Uncertainty is based on fleet-wide data and is expressed to a 99.73% level of confidence ($k=3$).

The instrument results before and after any adjustment are found in the associated pre and post stability checks.

TRACEABILITY INFORMATION

This instrument was calibrated using solutions prepared by Alcohol Countermeasure Systems, Inc. (ACS). ACS prepared and certified these CRMs in accordance with ISO 17034 and ISO/IEC 17025 Standards.

Simulator temperatures are traceable to NIST. Simulator temperatures are checked with NIST traceable digital thermometers calibrated by Precision Metrology in accordance with ISO/IEC 17025 standards.

Dry gas control measurements are traceable to NIST through the use of CRMs supplied by an accredited CRM supplier. The supplier of dry gas standard controls prepared and certified the CRMs in accordance with ISO Guide 34 and ISO/IEC 17025 standards.

This document shall not be reproduced except in full, without written approval of the Florida Department of Law Enforcement Alcohol Testing Program.

Digitally signed by S. LeAndra
Higginbotham
Date: 2026.08.18 18:38:00 -0400

08/13/2026

Date

LEANDRA HIGGINBOTHAM,

Department Inspector

FDLE/ATP Form 69 August 2026
Issuing Authority: Alcohol Testing Program

Service • Integrity • Respect • Quality